

IPSL-G0500-5 Information

Part Number IPSL-G0500-5 Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE 0-.5BARG 4-20MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPSL-G0500-5 Specifications

Manufacturer Part NumberIPSL-G0500-5ManufacturerCynergy 3CategorySensors, TransducersPackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure7.25 PSI (50 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series IPSL Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Manufacturer Part Number	IPSL-G0500-5
Pressure Sensors, Transducers Package Cylinder Series IPSL Pressure Type Vented Gauge Operating Pressure 7.25 PSI (50 kPa) Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure7.25 PSI (50 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder	Category	Sensors, Transducers
SeriesIPSLPressure TypeVented GaugeOperating Pressure7.25 PSI (50 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 7.25 PSI (50 kPa) Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Series	IPSL
Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Pressure Type	Vented Gauge
Output $4mA \sim 20mA$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $Male - 1/4" (6.35mm) \text{ BSP}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $Connector$ Maximum Pressure $Connector$ Operating Temperature $Connector$ Package / Case $Cylinder$	Operating Pressure	7.25 PSI (50 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $\text{Male - 1/4" (6.35 mm) BSP}$ Port Style Threaded Features $\text{Amplified Output, Temperature Compensated}}$ Termination Style Connector Maximum Pressure $72.52 \text{ PSI (500 kPa)}$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / Case Cylinder	Output Type	Analog Current
Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $Male - 1/4$ " (6.35mm) BSP Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / Case $Cylinder$	Output	4mA ~ 20mA
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style Connector Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / Case Cylinder	Port Style	Threaded
Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / CaseCylinder	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 80°C Package / Case Cylinder	Termination Style	Connector
Package / Case Cylinder	Maximum Pressure	72.52 PSI (500 kPa)
	Operating Temperature	-20°C ~ 80°C
Supplier Device Package -	Package / Case	Cylinder
	Supplier Device Package	-
Report errors?		Report errors?

IPSL-G0500-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSL-G0500-5 Payment Methods





















IPSL-G0500-5 Shipping Methods













If you have any question about IPSL-G0500-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com