

IPSL-G0750-D Information

Part Number IPSL-G0750-D Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE 0-.75BARG .5-4.5

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPSL-G0750-D Specifications

Manufacturer Part Number IPSL-G0750-D Manufacturer Cynergy 3 Category Sensors, Transducers Package Cylinder Series IPSL Pressure Type Vented Gauge Operating Pressure 10.88 PSI (75 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	IPSL-G0750-D
Package Cylinder Series IPSL Pressure Type Vented Gauge Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 80°C Package / Case Suppline Device Package Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cyent Sage (Cylinder) Cylinder Cylinder Cyent Sage (Cylinder) Cylinder Cylinder Cyent Sage (Cylinder) Cylinder Cylinder	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSLPressure TypeVented GaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) BSP Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Supplier Device Package - 10.88 PSI (75 kPa) Analog Voltage Analog Voltage Analog Voltage Analog Voltage 40.25% Analog Voltage 40.25% Analog Voltage 40.25% Accuracy 40.25% Accuracy 40.25% Amplified Output, Temperature Compensated Connector 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Cylinder Supplier Device Package	Series	IPSL
Output Type Output Outp	Pressure Type	Vented Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	10.88 PSI (75 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $Male - 1/4" (6.35\text{mm}) \text{ BSP}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / Case $Cylinder$ Supplier Device Package $-$	Output Type	Analog Voltage
Voltage - Supply Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Output	0.5 V ~ 4.5 V
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	72.52 PSI (500 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 80°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

IPSL-G0750-D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSL-G0750-D Payment Methods



















IPSL-G0750-D Shipping Methods













If you have any question about IPSL-G0750-D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com