

IPSLAT-G0050-5

IPSLAT-G0050-5 Information

Containance can ber	Part Number Manufacturer Category Description Package	IPSLAT-G0050-5 Cynergy 3 Sensors, Transducers Pressure Sensors, Transducers PRESSURE TRANS 0-50MBARG 4-20MA - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSLAT-G0050-5 Specifications

Manufacturer Cynergy 3 Category Sensors, Transducers Pressure Sensors, Transducers Pressure Sensors, Transducers Package - Series IPSLAT Pressure Type Gauge Operating Pressure 0.72 PSI (4.98 kPa) Output Type Analog Current Output Type 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Syle Amplified Output, Temperature Compensated Features Amplified Output, Temperature Compensated Operating Temperature 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 75°C Package / Case -		
CategorySeriors, TransducersPackage-Package-SeriesIPSLATPressure TypeGaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedComector20.01 PSI (200 kPa)Operating Temperature-0°C ~ 75°CPackage / Case-Supplier Device Package-Supplier Device Package-	Manufacturer Part Number	IPSLAT-G0050-5
Pressure Sensors, TransducersPackage-SeriesIPSLATPressure TypeGaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedComector29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-Supplier Device Package-	Manufacturer	Cynergy 3
Package-SeriesIPSLATPressure TypeGaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput Que4 mA ~ 20 mAAccuracy±0.25%Voltage - SupplyIo V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort SyleThreadedFeaturesAmplified Output, Temperature CompensatedPortentSonectorMaximum Pressure9.01 PSI (200 kPa)Operating Temperature-0°C ~ 75°CPackage / Case-Supplier Device Package-Supplier Device Package-	Category	Sensors, Transducers
SeriesIPSLATPressure TypeGaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeGaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput Quest4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Package	-
Operating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Series	IPSLAT
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Pressure Type	Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Operating Pressure	0.72 PSI (4.98 kPa)
Accuracy±0.25%Accuracy10 V ~ 28 VVoltage - SupplyMale - 1/4" (6.35mm) NPTPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Output Type	Analog Current
Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Voltage - Supply	10 V ~ 28 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Port Size	Male - 1/4" (6.35mm) NPT
Termination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Port Style	Threaded
Maximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-Automatic-Package / Case-Supplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-Supplier Device Package-	Termination Style	Connector
Package / Case - Supplier Device Package -	Maximum Pressure	29.01 PSI (200 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 75°C
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

IPSLAT-G0050-5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSLAT-G0050-5 Payment Methods



IPSLAT-G0050-5 Shipping Methods



If you have any question about IPSLAT-G0050-5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com