



IPSLAT-G0750-5 Information

Heisener.com

Part Number IPSLAT-G0750-5

Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANS 0-750MBARG 4-20MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPSLAT-G0750-5 Specifications

Manufacturer Part Number IPSLAT-G0750-5 Manufacturer Cynergy 3 Category Sensors, Transducers Package - Series IPSLAT Pressure Type Gauge Operating Pressure 10.88 PSI (75 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package - Report errors?		
Category Sensors, Transducers Pressure Sensors, Transducers Package - Series IPSLAT Pressure Type Gauge Operating Pressure 10.88 PSI (75 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package	Manufacturer Part Number	IPSLAT-G0750-5
Package - Series IPSLAT Pressure Type Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure -20°C ~ 75°C Package / Case Supplier Device Package Pressure Sensors, Transducers IPSLAT PASSURE PASSUR PASSUR	Manufacturer	Cynergy 3
Package - IPSLAT Pressure Type Gauge Operating Pressure 10.88 PSI (75 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature - 20°C ~ 75°C Package / Case - Supplier Device Package	Category	Sensors, Transducers
SeriesIPSLATPressure TypeGaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeGaugeOperating Pressure10.88 PSI (75 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure72.52 PSI (500 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Package	-
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package - 10.88 PSI (75 kPa) Analog Current 4 mA ~ 20 mA 5 voltage - Supply 10 V ~ 28 V Amplified Output, Temperature Compensated - 20°C ~ 75°C Package / Case - Supplier Device Package	Series	IPSLAT
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Pressure Type	Gauge
Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Operating Pressure	10.88 PSI (75 kPa)
Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Output Type	Analog Current
Voltage - Supply $10\ V \sim 28\ V$ Port Size $Male - 1/4"\ (6.35mm)\ NPT$ Port Style $Threaded$ Features $Amplified\ Output,\ Temperature\ Compensated$ Termination Style $Connector$ $Maximum\ Pressure$ $72.52\ PSI\ (500\ kPa)$ $Operating\ Temperature$ $-20^{\circ}C \sim 75^{\circ}C$ $Package\ /\ Case$ $-$ Supplier\ Device\ Package	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Voltage - Supply	10 V ~ 28 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Connector Maximum Pressure 72.52 PSI (500 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Port Style	Threaded
Maximum Pressure $72.52 \text{ PSI } (500 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Package / Case-Supplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Termination Style	Connector
Package / Case - Supplier Device Package -	Maximum Pressure	72.52 PSI (500 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 75°C
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

IPSLAT-G0750-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSLAT-G0750-5 Payment Methods





















IPSLAT-G0750-5 Shipping Methods













If you have any question about IPSLAT-G0750-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com