

IPSSAT-G5000-5C

IPSSAT-G5000-5C Information



For Reference Only

Part Number	IPSSAT-G5000-5C
Manufacturer	Cynergy 3
Category	Sensors, Transducers Pressure Sensors, Transducers
Description	PRESSURE TRANS 0-5BARG 4-20MA
Package	Cylinder, Threaded
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSSAT-G5000-5C Specifications

Manufacturer Part NumberIPSSAT-G5000-5CManufacturerCynergy 3CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinder, ThreadedSeriesIPSSPressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Yoltage - SupplySvaledPort SizeMale - 3/4" (19.05mm) BSPPort StyleAmplified Output, Temperature CompensatedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, Threaded	
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinder, ThreadedSeriesIPSSPressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeThreadedPort StyleConnector, 4-PinFeaturesAmplified Output, Temperature CompensatedFeatures145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Pressure Sensors, TransducersPackageCylinder, ThreadedSeriesIPSSPressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
PackageCylinder, ThreadedSeriesIPSSPressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMarinum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
SeriesIPSSPressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Pressure TypeSealed GaugeOperating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Operating Pressure72.52 PSI (500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Accuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Port SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Termination StyleConnector, 4-PinMaximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Maximum Pressure145.04 PSI (1000 kPa)Operating Temperature-20°C ~ 80°C	
Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$	
Package / Case Cylinder, Threaded	
Supplier Device Package -	
I	Report errors?

IPSSAT-G5000-5C Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSSAT-G5000-5C Payment Methods



IPSSAT-G5000-5C Shipping Methods



If you have any question about IPSSAT-G5000-5C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com