

IPSSAT-GM1P1-5C

IPSSAT-GM1P1-5C Information



Part Number	IPSSAT-GM1P1-5C	
Manufacturer	Cynergy 3	
Category	Sensors, Transducers Pressure Sensors, Transducers	
Description	PRESSURE TRANS -1-1 BARG 4-20MA	
Package	Cylinder, Threaded	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSSAT-GM1P1-5C Specifications

ManufacturerCynergy 3CategorySensors, TransducersPackageCylinder, ThreadedPackageCylinder, ThreadedSeriesIPSSPressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Type9 V ~ 32 VVoltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseSupplier Device PackageSupplier Device Package-		
CategorySensors, TransducersPressure Sensors, TransducersPackageCylinder, ThreadedSeriesIPSSPressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Type4mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / Casecylinder, ThreadedSupplier Device Package-	Manufacturer Part Number	IPSSAT-GM1P1-5C
Pressure Sensors, TransducersPackageCylinder, ThreadedSeriesIPSSPressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / Casecylinder, ThreadedSupplier Device Package-	Manufacturer	Cynergy 3
PackageCylinder, ThreadedSeriesIPSSPressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style£0.25% (19.05 kPa)Operating Temperature20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSSPressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Queue4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style£72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeDifferential/Vented GaugeOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput Queut4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Styleconnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / Casecylinder, ThreadedSupplier Device Package-	Package	Cylinder, Threaded
Operating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Series	IPSS
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Pressure Type	Differential/Vented Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Operating Pressure	±14.5 PSI (±100 kPa)
Accuracy±0.25%Accuracy9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Output Type	Analog Current
Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Voltage - Supply	9 V ~ 32 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Port Size	Male - 3/4" (19.05mm) BSP
Termination StyleConnector, 4-PinMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Port Style	Threaded
Maximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 80°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Termination Style	Connector, 4-Pin
Package / Case Cylinder, Threaded Supplier Device Package -	Maximum Pressure	±72.52 PSI (±500 kPa)
Supplier Device Package -	Operating Temperature	$-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
	Package / Case	Cylinder, Threaded
Report errors?	Supplier Device Package	-
		Report errors?

IPSSAT-GM1P1-5C Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSSAT-GM1P1-5C Payment Methods



IPSSAT-GM1P1-5C Shipping Methods



If you have any question about IPSSAT-GM1P1-5C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com