

IPSU-G1000-5 Information



For Reference Only

Part Number IPSU-G1000-5 Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRSSR TRNS 0-1BR 4-20MA DIN

Package Probe

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPSU-G1000-5 Specifications

Manufacturer Part Number IPSU-G1000-5 Manufacturer Cynergy 3 Category Sensors, Transducers Package Probe Series IPSU Pressure Type Vented Gauge Operating Pressure 14.5 PSI (100 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	-	
Category Sensors, Transducers Pressure Sensors, Transducers Probe Series IPSU Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure Operating Temperature - 20°C ~ 80°C Package / Case Supplier Device Package Probe	Manufacturer Part Number	IPSU-G1000-5
Package Probe Series IPSU Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package	Manufacturer	Cynergy 3
PackageProbeSeriesIPSUPressure TypeVented GaugeOperating Pressure14.5 PSI (100 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe	Category	Sensors, Transducers
SeriesIPSUPressure TypeVented GaugeOperating Pressure14.5 PSI (100 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure14.5 PSI (100 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe	Package	Probe
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 80°C Package / Case Supplier Device Package Probe	Series	IPSU
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Pressure Type	Vented Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe	Operating Pressure	14.5 PSI (100 kPa)
Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Output Type	Analog Current
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 80°C Package / Case Probe Supplier Device Package Probe	Port Style	Threaded
Maximum Pressure-Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 80°CPackage / CaseProbeSupplier Device PackageProbe	Termination Style	Connector
Package / Case Probe Supplier Device Package Probe	Maximum Pressure	-
Supplier Device Package Probe	Operating Temperature	-20°C ~ 80°C
	Package / Case	Probe
Report errors?	Supplier Device Package	Probe
		Report errors?

IPSU-G1000-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSU-G1000-5 Payment Methods



















IPSU-G1000-5 Shipping Methods













If you have any question about IPSU-G1000-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com