

IPSUAT-GP030-5

IPSUAT-GP030-5 Information



Part Number	IPSUAT-GP030-5	
Manufacturer	Cynergy 3	
Category	Sensors, Transducers Pressure Sensors, Transducers	
Description	PRESSURE TRANS 0-30PSIG 4-20MA	
Package	Chassis Mount	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSUAT-GP030-5 Specifications

Manufacturer Part NumberIPSUAT-GP030-5ManufacturerCynerg 3CategorySensors, TransducersPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput Type10 V ~ 28 VVoltage - SupplyIntracadedPort StyleMale 1/4" (6.35mm) NPTPort StyleConnectorMaximum Pressure60 PSI (13.69 kPa)Operating Temperature20°C ~ 75°CPackage / CaseChassis MountSupplier Device PackageIntracuterPackage / CaseChassis Mount		
CategorySensors, TransducersPackageChassis MountPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleConnectorFeaturesAmplified Output, Temperature CompensatedTermination Style60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / Casec.Supplier Device Package-	Manufacturer Part Number	IPSUAT-GP030-5
PackagePressure Sensors, TransducersPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-00°C ~ 75°CPackage / Case-Supplier Device Package-	Manufacturer	Cynergy 3
PackageChasis MountSeriesIPSUATPressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - SupplyNale - 1/4" (6.35mm) NPTPort SizeMale - 1/4" (6.35mm) NPTPort StyleConnectorFeaturesAnplified Output, Temperature CompensatedOperating Temperature60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Category	Sensors, Transducers
SeriesIPSUATPressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAOutput±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedOperating Temperature60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / Casec.Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeGaugeOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedPort nination Style60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / Case.Supplier Device Package.	Package	Chassis Mount
Operating Pressure30 PSI (206.84 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Series	IPSUAT
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Pressure Type	Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Operating Pressure	30 PSI (206.84 kPa)
Accuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Output Type	Analog Current
Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Voltage - Supply	10 V ~ 28 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Port Size	Male - 1/4" (6.35mm) NPT
Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Port Style	Threaded
Maximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Termination Style	Connector
Package / Case Chassis Mount Supplier Device Package -	Maximum Pressure	60 PSI (413.69 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 75°C
	Package / Case	Chassis Mount
Report err	Supplier Device Package	-
1		Report errors?

IPSUAT-GP030-5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSUAT-GP030-5 Payment Methods



IPSUAT-GP030-5 Shipping Methods



If you have any question about IPSUAT-GP030-5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com