

IPSUAT-GP3K6-5

IPSUAT-GP3K6-5 Information



IPSUAT-GP3K6-5
Cynergy 3
Sensors, Transducers Pressure Sensors, Transducers
PRESSURE TRANS 0-3600PSIG 4-20MA
Chassis Mount
For the pricing/inventory/lead time, please contact us
Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSUAT-GP3K6-5 Specifications

ManufacturerCynergy 3CategorySensors, TransducersPressure Sensors, TransducersPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedConnector6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis Mount		
CategorySensors, TransducersPressure Sensors, TransducersPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort SiyleThreadedFeaturesAmplified Output, Temperature CompensatedConnector6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / Casechassis MountSupplier Device Package-	Manufacturer Part Number	IPSUAT-GP3K6-5
Pressure Sensors, TransducersPackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFeatures6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Manufacturer	Cynergy 3
PackageChassis MountSeriesIPSUATPressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesGonectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseGnasis MountSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSUATSeriesGaugePressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedConnector6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / Casec.Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeGaugeOperating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Queue4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedConnector6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-	Package	Chassis Mount
Operating Pressure3600 PSI (24821.13 kPa)Output TypeAnalog CurrentOutput Qutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Series	IPSUAT
Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedConnectorConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Pressure Type	Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Operating Pressure	3600 PSI (24821.13 kPa)
Accuracy±0.25%Accuracy10 V ~ 28 VVoltage - SupplyMale - 1/4" (6.35mm) NPTPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFeaturesConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Output Type	Analog Current
Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFermination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Voltage - Supply	10 V ~ 28 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Port Size	Male - 1/4" (6.35mm) NPT
Termination StyleConnectorMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Port Style	Threaded
Maximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 75°CPackage / CaseChassis MountSupplier Device Package-	Termination Style	Connector
Package / Case Chassis Mount Supplier Device Package -	Maximum Pressure	6000 PSI (41368.54 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 75°C
	Package / Case	Chassis Mount
Report errors?	Supplier Device Package	-
		Report errors?

IPSUAT-GP3K6-5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSUAT-GP3K6-5 Payment Methods



IPSUAT-GP3K6-5 Shipping Methods



If you have any question about IPSUAT-GP3K6-5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com