

IR2104S Information



For Reference Only

Part Number IR2104S

Manufacturer Infineon Technologies

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC DRIVER HIGH/LOW SIDE 8-SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IR2104S Specifications

Manufacturer Part Number IR2104S Manufacturer Infineon Technologies Category Integrated Circuits (ICs) Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type IGBT, N-Channel MOSFET Voltage - Supply 10 V ~ 20 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) 210mA, 360mA Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 600V Rise / Fall Time (Typ) 100ns, 50ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
CategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeIGBT, N-Channel MOSFETVoltage - Supply10 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)210mA, 360mAInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)600VRise / Fall Time (Typ)100ns, 50nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Manufacturer Part Number	IR2104S
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type IGBT, N-Channel MOSFET Voltage - Supply 10 V ~ 20 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) 210mA, 360mA Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 600V Rise / Fall Time (Typ) 100ns, 50ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Infineon Technologies
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeIGBT, N-Channel MOSFETVoltage - Supply10 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)210mA, 360mAInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)600VRise / Fall Time (Typ)100ns, 50nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeIGBT, N-Channel MOSFETVoltage - Supply10 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)210mA, 360mAInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)600VRise / Fall Time (Typ)100ns, 50nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Synchronous Number of Drivers 2 Gate Type IGBT, N-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Synchronous Number of Drivers 2 Gate Type IGBT, N-Channel MOSFET Voltage - Supply 10 V ~ 20 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) 210mA, 360mA Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 600V Rise / Fall Time (Typ) 100ns, 50ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers2Gate TypeIGBT, N-Channel MOSFETVoltage - Supply10 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)210mA, 360mAInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)600VRise / Fall Time (Typ)100ns, 50nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Driven Configuration	Half-Bridge
Gate Type IGBT, N-Channel MOSFET Voltage - Supply 10 V ~ 20 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 100ns, 50ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Synchronous
Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)210mA, 360mAInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)600VRise / Fall Time (Typ)100ns, 50nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Gate Type	IGBT, N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Operating Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	10 V ~ 20 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 3V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	210mA, 360mA
Rise / Fall Time (Typ) 100ns, 50ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	600V
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	100ns, 50ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

IR2104S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IR2104S Payment Methods





















IR2104S Shipping Methods













If you have any question about IR2104S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com