



## **IRF1405ZTRL Information**



For Reference Only

Part Number IRF1405ZTRL

Manufacturer Vishay Siliconix

Category Discrete Semiconductor Products

Transistors - FETs, MOSFETs - Single

**Description** MOSFET N-CH 55V 75A TO-220AB

Package TO-220-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **IRF1405ZTRL Specifications**

Manufacturer Part Number         IRF1405ZTRL           Manufacturer         Vishay Siliconix           Category         Discrete Semiconductor Products           Transistors - FETs, MOSFETs - Single           Package         TO-220-3           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         55V           Current - Continuous Drain (Id) @ 25°C         75A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         10V           Vgs(th) (Max) @ Id         4V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         180nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         4780pF @ 25V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         230W (Tc)           Rds On (Max) @ Id, Vgs         4.9 mOhm @ 75A, 10V           Operating Temperature         -55°C ~ 175°C (TJ)           Mounting Type         Through Hole           Supplier Device Package         TO-220AB           Package / Case         TO-220-3		
Category         Discrete Semiconductor Products           Package         TO-220-3           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         55V           Current - Continuous Drain (Id) @ 25°C         75A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         10V           Vgs(th) (Max) @ Id         4V @ 250µA           Gate Charge (Qg) (Max) @ Vgs         180nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         4780pF @ 25V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         230W (Tc)           Rds On (Max) @ Id, Vgs         4.9 mOhm @ 75A, 10V           Operating Temperature         -55°C ~ 175°C (TJ)           Mounting Type         Through Hole           Supplier Device Package         TO-220AB           Package / Case         TO-220AB	Manufacturer Part Number	IRF1405ZTRL
Package         TO-220-3           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         55V           Current - Continuous Drain (Id) @ 25°C         75A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         10V           Vgs(th) (Max) @ Id         4V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         180nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         4780pF @ 25V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         230W (Tc)           Rds On (Max) @ Id, Vgs         4.9 mOhm @ 75A, 10V           Operating Temperature         -55°C ~ 175°C (TJ)           Mounting Type         Through Hole           Supplier Device Package         TO-220AB           Package / Case         TO-220-3	Manufacturer	Vishay Siliconix
Package         TO-220-3           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         55 V           Current - Continuous Drain (Id) @ 25°C         75A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         10V           Vgs(th) (Max) @ Id         4V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         180nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         4780pF @ 25V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         230W (Tc)           Rds On (Max) @ Id, Vgs         4.9 mOhm @ 75A, 10V           Operating Temperature         -55°C ~ 175°C (TJ)           Mounting Type         Through Hole           Supplier Device Package         TO-220AB           Package / Case         TO-220-3	Category	Discrete Semiconductor Products
Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         55V           Current - Continuous Drain (Id) @ 25°C         75A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         10V           Vgs(th) (Max) @ Id         4V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         180nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         4780pF @ 25V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         230W (Tc)           Rds On (Max) @ Id, Vgs         4.9 mOhm @ 75A, 10V           Operating Temperature         -55°C ~ 175°C (TJ)           Mounting Type         Through Hole           Supplier Device Package         TO-220AB           Package / Case         TO-220-3		Transistors - FETs, MOSFETs - Single
FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C75A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs180nC @ 10VInput Capacitance (Ciss) (Max) @ Vds4780pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	Package	TO-220-3
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C75A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs180nC @ 10VInput Capacitance (Ciss) (Max) @ Vds4780pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	Series	-
Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C75A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs180nC @ 10VInput Capacitance (Ciss) (Max) @ Vds4780pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	FET Type	N-Channel
Current - Continuous Drain (Id) @ 25°C75A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs180nC @ 10VInput Capacitance (Ciss) (Max) @ Vds4780pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs180nC @ 10VInput Capacitance (Ciss) (Max) @ Vds4780pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	Drain to Source Voltage (Vdss)	55V
Vgs(th) (Max) @ Id	Current - Continuous Drain (Id) @ 25°C	75A (Tc)
Gate Charge (Qg) (Max) @ Vgs  Input Capacitance (Ciss) (Max) @ Vds  4780pF @ 25V  Vgs (Max)  ±20V  FET Feature  - Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  4.9 mOhm @ 75A, 10V  Operating Temperature  -55°C ~ 175°C (TJ)  Mounting Type  Through Hole  Supplier Device Package  TO-220AB  Package / Case  TO-220-3	Drive Voltage (Max Rds On, Min Rds On)	10V
Input Capacitance (Ciss) (Max) @ Vds  4780pF @ 25V  Vgs (Max)  E20V  FET Feature  - Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  4.9 mOhm @ 75A, 10V  Operating Temperature  -55°C ~ 175°C (TJ)  Mounting Type  Through Hole  Supplier Device Package  TO-220AB  Package / Case  TO-220-3	Vgs(th) (Max) @ Id	4V @ 250μA
Vgs (Max)±20VFET Feature-Power Dissipation (Max)230W (Tc)Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	Gate Charge (Qg) (Max) @ Vgs	180nC @ 10V
FET Feature - Case - Case - Case - TO-220-3	Input Capacitance (Ciss) (Max) @ Vds	4780pF @ 25V
Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  4.9 mOhm @ 75A, 10V  Operating Temperature  -55°C ~ 175°C (TJ)  Mounting Type  Through Hole  Supplier Device Package  TO-220AB  Package / Case  TO-220-3	Vgs (Max)	±20V
Rds On (Max) @ Id, Vgs4.9 mOhm @ 75A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220ABPackage / CaseTO-220-3	FET Feature	-
Operating Temperature  -55°C ~ 175°C (TJ)  Mounting Type  Through Hole  Supplier Device Package  TO-220AB  Package / Case  TO-220-3	Power Dissipation (Max)	230W (Tc)
Mounting Type Through Hole Supplier Device Package TO-220AB Package / Case TO-220-3	Rds On (Max) @ Id, Vgs	4.9 mOhm @ 75A, 10V
Supplier Device Package TO-220AB Package / Case TO-220-3	Operating Temperature	-55°C ~ 175°C (TJ)
Package / Case TO-220-3	Mounting Type	Through Hole
-	Supplier Device Package	TO-220AB
Report errors?	Package / Case	TO-220-3
		Report errors?

#### **IRF1405ZTRL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **IRF1405ZTRL Payment Methods**



















## **IRF1405ZTRL Shipping Methods**













If you have any question about IRF1405ZTRL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com