



IRF9Z24NLPBF Information



For Reference Only

Part Number IRF9Z24NLPBF
Manufacturer Infineon Technologies

Category Discrete Semiconductor Products
Transistors - FETs, MOSFETs - Single

Description MOSFET P-CH 55V 12A TO-262

Package TO-262-3 Long Leads, I2Pak, TO-262AA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IRF9Z24NLPBF Specifications

Manufacturer Part Number IRF9Z24NLPBF Manufacturer Infineon Technologies Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package TO-262-3 Long Leads, 12Pak, TO-262AA Series HEXFET? FET Type P-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 55V Current - Continuous Drain (Id) @ 25°C 12A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250μA Gate Charge (Qg) (Max) @ Vgs 19nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 350pF @ 25V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 3.8W (Ta), 45W (Tc) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, 12Pak, TO-262AA		
CategoryDiscrete Semiconductor ProductsTransistors - FETs, MOSFETs - SinglePackageTO-262-3 Long Leads, 12Pak, TO-262AASeriesHEXFET?FET TypeP-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C12A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs19nC @ 10VInput Capacitance (Ciss) (Max) @ Vds350pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TI)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, 12Pak, TO-262AA	Manufacturer Part Number	IRF9Z24NLPBF
Package TO-262-3 Long Leads, 12Pak, TO-262AA Series HEXFET? FET Type P-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 55V Current - Continuous Drain (Id) @ 25°C 12A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250μA Gate Charge (Qg) (Max) @ Vgs 19nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 350pF @ 25V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 3.8W (Ta), 45W (Tc) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Manufacturer	Infineon Technologies
Package TO-262-3 Long Leads, 12Pak, TO-262AA Series HEXFET? FET Type P-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 55V Current - Continuous Drain (Id) @ 25°C 12A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250μA Gate Charge (Qg) (Max) @ Vgs 19nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 350pF @ 25V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 3.8W (Ta), 45W (Tc) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, 12Pak, TO-262AA	Category	Discrete Semiconductor Products
SeriesHEXFET?FET TypeP-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C12A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs19nC @ 10VInput Capacitance (Ciss) (Max) @ Vds350pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, 12Pak, TO-262AA		Transistors - FETs, MOSFETs - Single
FET Type P-Channel MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 55V Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs 19nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 350pF @ 25V Vgs (Max) FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case Possibation (Max) P-Channel MOSFET (Metal Oxide) PS-Channel MOSFET (Metal Oxide) PS-Channel MOSFET (Metal Oxide) PS-Channel P-Channel POWSFET (Metal Oxide) 12A (Tc) PSV 19C PSV 250μA 4V @ 250μA 4V @ 250μA 4V @ 250μA 550F @ 25V 25V 25V 25V 25V 25V 25V 25V	Package	TO-262-3 Long Leads, I2Pak, TO-262AA
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C12A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs19nC @ 10VInput Capacitance (Ciss) (Max) @ Vds350pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, 12Pak, TO-262AA	Series	HEXFET?
Drain to Source Voltage (Vdss)55VCurrent - Continuous Drain (Id) @ 25°C12A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs19nC @ 10VInput Capacitance (Ciss) (Max) @ Vds350pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, 12Pak, TO-262AA	FET Type	P-Channel
Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs 19nC @ 10V Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) ±20V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature Supplier Device Package Package / Case 12A (Tc) 10V 10V 4V @ 250μA 4V @ 250μA 350pF @ 25V 25V 25V 25V 27V 27V 27V 27V	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs19nC @ 10VInput Capacitance (Ciss) (Max) @ Vds350pF @ 25VVgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, 12Pak, TO-262AA	Drain to Source Voltage (Vdss)	55V
Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) FET Feature Power Dissipation (Max) As W (Ta), 45W (Tc) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature Supplier Device Package Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Current - Continuous Drain (Id) @ 25°C	12A (Tc)
Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) #ET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature #Mounting Type Through Hole Supplier Device Package Package / Case 19nC @ 10V 350pF @ 25V **EQUIVATION** **EQUIVATION** **EQUIVATION** **Input Capacitance (Ciss) (Max) @ Vds **EQUIVATION** **EQUIVATION** **Input Capacitance (Ciss) (Max) @ Vds **EQUIVATION** **EQUIVATION** **Input Capacitance (Ciss) (Max) @ Vds **Input Capacitance (Ciss) (Max) & V	Drive Voltage (Max Rds On, Min Rds On)	10V
Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) E20V FET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, 12Pak, TO-262AA	Vgs(th) (Max) @ Id	4V @ 250μA
Vgs (Max)±20VFET Feature-Power Dissipation (Max)3.8W (Ta), 45W (Tc)Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, I2Pak, TO-262AA	Gate Charge (Qg) (Max) @ Vgs	19nC @ 10V
FET Feature - Power Dissipation (Max) 3.8W (Ta), 45W (Tc) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Input Capacitance (Ciss) (Max) @ Vds	350pF @ 25V
Power Dissipation (Max) Rds On (Max) @ Id, Vgs 175 mOhm @ 7.2A, 10V Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Vgs (Max)	±20V
Rds On (Max) @ Id, Vgs175 mOhm @ 7.2A, 10VOperating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-262Package / CaseTO-262-3 Long Leads, I2Pak, TO-262AA	FET Feature	-
Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Power Dissipation (Max)	3.8W (Ta), 45W (Tc)
Mounting Type Through Hole Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Rds On (Max) @ Id, Vgs	175 mOhm @ 7.2A, 10V
Supplier Device Package TO-262 Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Operating Temperature	-55°C ~ 175°C (TJ)
Package / Case TO-262-3 Long Leads, I2Pak, TO-262AA	Mounting Type	Through Hole
	Supplier Device Package	TO-262
Report errors?	Package / Case	TO-262-3 Long Leads, I2Pak, TO-262AA
		Report errors?

IRF9Z24NLPBF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IRF9Z24NLPBF Payment Methods



















IRF9Z24NLPBF Shipping Methods













If you have any question about IRF9Z24NLPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com