

**ISC1812EB271J Information**


For Reference Only

**Part Number** [ISC1812EB271J](#)  
**Manufacturer** Vishay Dale  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 270UH 101MA 6.9 OHM  
**Package** 1812 (4532 Metric)  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**ISC1812EB271J Specifications**

Manufacturer Part Number	<a href="#">ISC1812EB271J</a>
Manufacturer	Vishay Dale
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	1812 (4532 Metric)
Series	ISC-1812
Type	Wirewound
Material - Core	Ferrite
Inductance	270µH
Tolerance	±5%
Current Rating	101mA
Current - Saturation	-
Shielding	Shielded
DC Resistance (DCR)	6.9 Ohm Max
Q @ Freq	40 @ 796kHz
Frequency - Self Resonant	4MHz
Ratings	-
Operating Temperature	-55°C ~ 125°C
Frequency - Test	796kHz
Features	-
Mounting Type	Surface Mount
Package / Case	1812 (4532 Metric)
Supplier Device Package	1812
Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)

Height - Seated (Max)

0.134" (3.40mm)

[Report errors?](#)

## ISC1812EB271J Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ISC1812EB271J Payment Methods



## ISC1812EB271J Shipping Methods



If you have any question about ISC1812EB271J, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)