



ISL6605IB-T Information



For Reference Only

Part Number ISL6605IB-T Manufacturer Intersil

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC MOSFET DRVR SYNC BUCK 8-SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ISL6605IB-T Specifications

Manufacturer Part Number ISL6605IB-T Manufacturer Intersil Category Integrated Circuits (ICs) PACKage 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH IV, 2V Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 33V Rise / Fall Time (Typ) 8ns, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
Category Package Integrated Circuits (ICs) PMIC - Gate Drivers Package PMIC - Gate Drivers Package Package Package Package Package Package Integrated Circuits (ICs) PMIC - Gate Drivers Package Package Package Package Package Integrated Circuits (ICs) PMIC - Gate Drivers Package	Manufacturer Part Number	ISL6605IB-T
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 33V Rise / Fall Time (Typ) 8ns, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Intersil
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)33VRise / Fall Time (Typ)8ns, 8nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)33VRise / Fall Time (Typ)8ns, 8nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 33V Rise / Fall Time (Typ) 8ns, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)33VRise / Fall Time (Typ)8ns, 8nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Driven Configuration	Half-Bridge
Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)33VRise / Fall Time (Typ)8ns, 8nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Channel Type	Synchronous
Voltage - Supply Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Sens, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.5 V ~ 5.5 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Surface Mount Package / Case Supplier Device Package Non-Inverting Non-Inverting Non-Inverting Surface Surface Surface Non-Inverting Surface Sur	Logic Voltage - VIL, VIH	1V, 2V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 8ns, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	2A, 2A
Rise / Fall Time (Typ) 8ns, 8ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	33V
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	8ns, 8ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

ISL6605IB-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ISL6605IB-T Payment Methods





















ISL6605IB-T Shipping Methods













If you have any question about ISL6605IB-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com