



ISL6612AECB-T Information



For Reference Only

Part Number ISL6612AECB-T

Manufacturer Intersil

Category Integrated Circuits (ICs)

PMIC - Gate Drivers

DescriptionIC MOSFET DRVR SYNC BUCK 8EPSOIC**Package**8-SOIC (0.154", 3.90mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ISL6612AECB-T Specifications

Manufacturer Part NumberISL6612AECB-TManufacturerIntersilCategoryIntegrated Circuits (ICs)Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10.8 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature0°C ~ 125°C (TI)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP			
Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 8-SOIC (0.154", 3.90mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10.8 V ~ 13.2 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 36V Rise / Fall Time (Typ) Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Manufacturer Part Number	ISL6612AECB-T	
Package 8-SOIC (0.154", 3.90mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10.8 V ~ 13.2 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 1.25A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 36V Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Manufacturer	Intersil	
Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10.8 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Category	Integrated Circuits (ICs)	
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10.8 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP		PMIC - Gate Drivers	
Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10.8 V ~ 13.2 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 1.25A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width) Exposed Pad	
Channel Type Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10.8 V ~ 13.2 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Series	-	
Number of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10.8 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Driven Configuration	Half-Bridge	
Gate TypeN-Channel MOSFETVoltage - Supply10.8 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Channel Type	Synchronous	
Voltage - Supply Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Number of Drivers	2	
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Gate Type	N-Channel MOSFET	
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Voltage - Supply	10.8 V ~ 13.2 V	
Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 36V Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Logic Voltage - VIL, VIH	-	
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Current - Peak Output (Source, Sink)	1.25A, 2A	
Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Input Type	Non-Inverting	
Operating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	High Side Voltage - Max (Bootstrap)	36V	
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Rise / Fall Time (Typ)	26ns, 18ns	
Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Operating Temperature	0°C ~ 125°C (TJ)	
Supplier Device Package 8-SOIC-EP	Mounting Type	Surface Mount	
	Package / Case	8-SOIC (0.154", 3.90mm Width) Exposed Pad	
Report errors?	Supplier Device Package	8-SOIC-EP	
			Report errors?

ISL6612AECB-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ISL6612AECB-T Payment Methods



















ISL6612AECB-T Shipping Methods













If you have any question about ISL6612AECB-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com