



### **ISL6613BEIBZ-T Information**



For Reference Only

Part Number ISL6613BEIBZ-T

Manufacturer Renesas Electronics America

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

**Description**IC MOSFET DRVR SYNC BUCK 8EPSOIC**Package**8-SOIC (0.154", 3.90mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ISL6613BEIBZ-T Specifications**

Manufacturer Part NumberISL6613BEIBZ-TManufacturerRenesas Electronics AmericaCategoryIntegrated Circuits (ICs)Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply7 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP		
Category  Integrated Circuits (ICs)  PMIC - Gate Drivers  Package  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Series  - Driven Configuration  Half-Bridge  Channel Type  Synchronous  Number of Drivers  2  Gate Type  N-Channel MOSFET  Voltage - Supply  7 V ~ 13.2 V  Logic Voltage - VIL, VIH  - Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  36V  Rise / Fall Time (Typ)  Operating Temperature  40°C ~ 125°C (TJ)  Mounting Type  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Manufacturer Part Number	ISL6613BEIBZ-T
Package 8-SOIC (0.154", 3.90mm Width) Exposed Pad  Series - Driven Configuration Half-Bridge Channel Type Synchronous  Number of Drivers 2 Gate Type N-Channel MOSFET  Voltage - Supply 7 V ~ 13.2 V  Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 1.25A, 2A  Input Type Non-Inverting  High Side Voltage - Max (Bootstrap) 36V  Rise / Fall Time (Typ) 26ns, 18ns  Operating Temperature -40°C ~ 125°C (TJ)  Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Manufacturer	Renesas Electronics America
Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply7 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply7 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP		PMIC - Gate Drivers
Driven Configuration  Half-Bridge  Channel Type  Synchronous  Number of Drivers  2  Gate Type  N-Channel MOSFET  Voltage - Supply  7 V ~ 13.2 V  Logic Voltage - VIL, VIH  - Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width) Exposed Pad
Channel Type Synchronous  Number of Drivers 2  Gate Type N-Channel MOSFET  Voltage - Supply 7 V ~ 13.2 V  Logic Voltage - VIL, VIH -  Current - Peak Output (Source, Sink) 1.25A, 2A  Input Type Non-Inverting  High Side Voltage - Max (Bootstrap) 36V  Rise / Fall Time (Typ) 26ns, 18ns  Operating Temperature -40°C ~ 125°C (TJ)  Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package 8-SOIC-EP	Series	-
Number of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply7 V ~ 13.2 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)1.25A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)36VRise / Fall Time (Typ)26ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Driven Configuration	Half-Bridge
Gate Type  N-Channel MOSFET  7 V ~ 13.2 V  Logic Voltage - VIL, VIH  - Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  Ao°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Channel Type	Synchronous
Voltage - Supply  Logic Voltage - VIL, VIH  - Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package	Voltage - Supply	7 V ~ 13.2 V
Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 36V Rise / Fall Time (Typ) 26ns, 18ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Logic Voltage - VIL, VIH	-
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  26ns, 18ns  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package  8-SOIC-EP	Current - Peak Output (Source, Sink)	1.25A, 2A
Rise / Fall Time (Typ)  26ns, 18ns  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package  8-SOIC-EP	Input Type	Non-Inverting
Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package  8-SOIC-EP	High Side Voltage - Max (Bootstrap)	36V
Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad  Supplier Device Package 8-SOIC-EP	Rise / Fall Time (Typ)	26ns, 18ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package 8-SOIC-EP	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width) Exposed Pad
Report errors?	Supplier Device Package	8-SOIC-EP
Report circles.		Report errors?

#### **ISL6613BEIBZ-T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# ISL6613BEIBZ-T Payment Methods



















## **ISL6613BEIBZ-T Shipping Methods**













If you have any question about ISL6613BEIBZ-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com