

ISM43362-M3G-L44-E-C2.5.0.2

ISM43362-M3G-L44-E-C2.5.0.2 Information

Part Number ISM43362-M3G-L44-E-C2.5.0.2

ManufacturerInventek SystemsCategoryRF/IF and RFID

RF Transceiver Modules

Description RF TXRX MODULE WIFI TRACE ANT

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ISM43362-M3G-L44-E-C2.5.0.2 Specifications

Manufacturer Part Number Manufacturer Inventek Systems RF/IF and RFID RF Transceiver Modules Package Module Series eS-WiFi?, WICED RF Family/Standard Protocol Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size IMB Flash Voltage - Supply 3.3V Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature 4-40°C ~ 85°C Package / Case Module	
RF/IF and RFID RF Transceiver Modules Package Module Series eS-WiFi?, WICED RF Family/Standard WiFi Protocol 802.11b/g/n Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
RF Transceiver Modules Package Module Series eS-WiFi?, WICED RF Family/Standard WiFi Protocol 802.11b/g/n Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Package	
Series eS-WiFi?, WICED RF Family/Standard WiFi Protocol 802.11b/g/n Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
RF Family/Standard Protocol 802.11b/g/n Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Protocol 802.11b/g/n Modulation 16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSK Frequency 2.4GHz Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Modulation16QAM, 64QAM, BPSK, CCK, DBPSK, DQPSK, OFDM, QPSKFrequency2.4GHzData Rate72.2MbpsPower - Output18dBmSensitivity-93dBmSerial InterfacesUARTAntenna TypeIntegrated, TraceMemory Size1MB FlashVoltage - Supply3.3VCurrent - Receiving-Current - Transmitting-Mounting TypeSurface MountOperating Temperature-40°C ~ 85°C	
Frequency Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Data Rate 72.2Mbps Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Power - Output 18dBm Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Sensitivity -93dBm Serial Interfaces UART Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Serial Interfaces Antenna Type Integrated, Trace Memory Size IMB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting Mounting Type Surface Mount Operating Temperature UART Integrated, Trace IMB Flash Surface Surface - Surface Surface For the surface - Surface Surfa	
Antenna Type Integrated, Trace Memory Size 1MB Flash Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Memory Size1MB FlashVoltage - Supply3.3VCurrent - Receiving-Current - Transmitting-Mounting TypeSurface MountOperating Temperature-40°C ~ 85°C	
Voltage - Supply Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature 3.3V	
Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 85°C	
Current - Transmitting-Mounting TypeSurface MountOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Mounting Type Surface Mount Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Pagkaga / Casa Madula	
rackage / Case iviolule	
Repo	Report errors?

ISM43362-M3G-L44-E-C2.5.0.2 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ISM43362-M3G-L44-E-C2.5.0.2 Payment Methods



















ISM43362-M3G-L44-E-C2.5.0.2 Shipping Methods













If you have any question about ISM43362-M3G-L44-E-C2.5.0.2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com