



ISO124U/1KG4 Information



For Reference Only

Part Number ISO124U/1KG4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

DescriptionIC OPAMP ISOLATION 50KHZ 8SOIC**Package**28-SOIC (0.295", 7.50mm Width) 8 Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ISO124U/1KG4 Specifications

Manufacturer Part Number Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 28-SOIC (0.295", 7.50mm Width) 8 Leads Series - Amplifier Type Isolation Number of Circuits 1 Output Type Slew Rate 2 V/µs Gain Bandwidth Product -3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 28-SOIC (0.295", 7.50mm Width) 8 Leads Series - Amplifier Type Isolation Number of Circuits 1 Output Type Slew Rate 2 V/µs Gain Bandwidth Product -3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 28-SOIC (0.295", 7.50mm Width) 8 Leads Series - Amplifier Type Isolation Number of Circuits Output Type - Slew Rate 2 V/µs Gain Bandwidth Product -3db Bandwidth 50kHz Current - Input Bias Voltage - Input Offset Current - Supply 5mA Current - Output / Channel Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Package 28-SOIC (0.295", 7.50mm Width) 8 Leads Series - Amplifier Type Isolation Number of Circuits 1 Output Type - Slew Rate 2 V/μs Gain Bandwidth Product - -3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Series - Amplifier Type Isolation Number of Circuits 1 Output Type - Slew Rate 2 V/μs Gain Bandwidth Product
Amplifier Type Isolation Number of Circuits 1 Output Type - Slew Rate 2 V/µs Gain Bandwidth Product3db Bandwidth SokHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Number of Circuits 1 Output Type - Slew Rate 2 $V/\mu s$ Gain Bandwidth Product3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \text{ V} \sim 18 \text{ V}$
Output Type - Slew Rate 2 $V/\mu s$ Gain Bandwidth Product
Slew Rate $2 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \text{ V} \sim 18 \text{ V}$
Gain Bandwidth Product -3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
-3db Bandwidth 50kHz Current - Input Bias - Voltage - Input Offset 20mV Current - Supply 5mA Current - Output / Channel 15mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Current - Input Bias-Voltage - Input Offset $20mV$ Current - Supply $5mA$ Current - Output / Channel $15mA$ Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \ V \sim 18 \ V$
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$
Current - Supply $5mA$ Current - Output / Channel $15mA$ Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \text{ V} \sim 18 \text{ V}$
Current - Output / Channel 15mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V
Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \text{ V} \sim 18 \text{ V}$
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Mounting Type Surface Mount
Package / Case 28-SOIC (0.295", 7.50mm Width) 8 Leads
Supplier Device Package 8-SOIC
Report error

ISO124U/1KG4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ISO124U/1KG4 Payment Methods





















ISO124U/1KG4 Shipping Methods













If you have any question about ISO124U/1KG4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com