



IWPTLU-GP005-00 Information

Part Number IWPTLU-GP005-00

Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE SENSOR WIFI LR ABS 0-5P

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IWPTLU-GP005-00 Specifications

Manufacturer Part NumberIWPTLU-GP005-00ManufacturerCynergy 3CategorySensors, TransducersPackageModuleSeriesIWPTLUPressure TypeSealed GaugeOperating Pressure5 PSI (34.47 kPa)Output Type-Output Type+0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort SyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule		
Category Sensors, Transducers Package Module Series IWPTLU Pressure Type Sealed Gauge Operating Pressure Output Type Output Wireless Accuracy Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Termination Style Maximum Pressure Operating Temperature - 20°C ~ 80°C Package / Case Module	Manufacturer Part Number	IWPTLU-GP005-00
Package Module Series IWPTLU Pressure Type Sealed Gauge Operating Pressure Output Type - Coutput Wireless Accuracy ±0.25% Voltage - Supply - Male - 1/4" (6.35mm) NPT Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style - Package / Case Module Supplier Device Package Module Supplier Device Package Module	Manufacturer	Cynergy 3
Package Module Series IWPTLU Pressure Type Sealed Gauge Operating Pressure 5 PSI (34.47 kPa) Output Type - Output Wireless Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style - Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature -20°C ~ 80°C Package / Case Module Supplier Device Package Module	Category	Sensors, Transducers
SeriesIWPTLUPressure TypeSealed GaugeOperating Pressure5 PSI (34.47 kPa)Output Type-OutputWirelessAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure5 PSI (34.47 kPa)Output Type-OutputWirelessAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Package	Module
Operating Pressure Output Type - Output Wireless Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Features - Termination Style Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature Package / Case Module Supplier Device Package Module	Series	IWPTLU
Output Type-OutputWirelessAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Pressure Type	Sealed Gauge
OutputWirelessAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Operating Pressure	5 PSI (34.47 kPa)
Accuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style-Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Output Type	-
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature Package / Case Module Supplier Device Package Module	Output	Wireless
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style - Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature -20°C ~ 80°C Package / Case Module Supplier Device Package Module	Accuracy	±0.25%
Port Style Threaded Features - Termination Style - Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature -20°C ~ 80°C Package / Case Module Supplier Device Package Module	Voltage - Supply	-
Features - Termination Style - Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature -20°C ~ 80°C Package / Case Module Supplier Device Package Module	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style - Maximum Pressure 75 PSI (517.11 kPa) Operating Temperature -20°C ~ 80°C Package / Case Module Supplier Device Package Module	Port Style	Threaded
Maximum Pressure75 PSI (517.11 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Features	-
Operating Temperature-20°C ~ 80°CPackage / CaseModuleSupplier Device PackageModule	Termination Style	-
Package / Case Module Supplier Device Package Module	Maximum Pressure	75 PSI (517.11 kPa)
Supplier Device Package Module	Operating Temperature	-20°C ~ 80°C
	Package / Case	Module
	Supplier Device Package	Module
Report errors?		Report errors?

IWPTLU-GP005-00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IWPTLU-GP005-00 Payment Methods



















IWPTLU-GP005-00 Shipping Methods













If you have any question about IWPTLU-GP005-00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com