



IXDI504SIA Information



For Reference Only

Part Number IXDI504SIA Manufacturer IXYS

Category Integrated Circuits (ICs)

PMIC - Gate Drivers

Description IC GATE DRIVER DUAL 4A 8-SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IXDI504SIA Specifications

Manufacturer Part Number IXDI504SIA Manufacturer IXYS Category Integrated Circuits (ICs) Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 9ns, 8ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
Category Package Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) Operating Temperature Operating Temperature Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer Part Number	IXDI504SIA
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 9ns, 8ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	IXYS
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeIGBT, N-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 30 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)9ns, 8nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeIGBT, N-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 30 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)9ns, 8nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Independent Number of Drivers 2 Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 2 Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 9ns, 8ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers2Gate TypeIGBT, N-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 30 VLogic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)9ns, 8nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Driven Configuration	Low-Side
Gate Type IGBT, N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 30 V Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 9ns, 8ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 3V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH0.8V, 3VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)9ns, 8nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Gate Type	IGBT, N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.5 V ~ 30 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 3V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 9ns, 8ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	4A, 4A
Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Input Type	Inverting
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	9ns, 8ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors

IXDI504SIA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IXDI504SIA Payment Methods



















IXDI504SIA Shipping Methods













If you have any question about IXDI504SIA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com