



J1006F01PNL Information

Heisener.com

Part Number J1006F01PNL

ManufacturerPulse Electronics NetworkCategoryConnectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 100 BASE-TX

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









J1006F01PNL Specifications

Manufacturer Part Number J1006F01PNL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J1 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	-	
Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J1 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Manufacturer Part Number	J1006F01PNL
Package-SeriesPULSEJACK? J1Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	Pulse Electronics Network
Package - Series PULSEJACK? J1 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Category	Connectors, Interconnects
SeriesPULSEJACK? J1Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Package	-
Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 1 10/100 Base-TX, AutoMDIX 10/100 Base-	Series	PULSEJACK? J1
Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Operating Temperature	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100 Base-TX, AutoMDIX
Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Orientation	90° Angle (Right)
LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 4 Contact Material April 4	Height Above Board	0.550" (13.97mm)
Shielding Shielded Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Green - Yellow
Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	4
Tab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded
Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Features	Board Guide
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Up
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
	Operating Temperature	0°C ~ 70°C
Report errors?		Report errors?

J1006F01PNL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

J1006F01PNL Payment Methods





















J1006F01PNL Shipping Methods













If you have any question about J1006F01PNL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com