



### J1026F01P Information

Heisener.com

Part Number J1026F01P

Manufacturer Pulse Electronics Network
Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

**Description** CONN MAGJACK 1PORT 100 BASE-TX

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# J1026F01P Specifications

Manufacturer Part NumberJ1026F01PManufacturerPulse Electronics NetworkCategoryConnectors, InterconnectsModular Connectors - Jacks With MagneticsPackage-SeriesPULSEJACK? J1Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.550" (13.97mm)LED ColorGreen - YellowNumber of Cores per Jack5ShieldingShieldedFeaturesBoard Guide
Category  Connectors, Interconnects  Modular Connectors - Jacks With Magnetics  Package  - Series  PULSEJACK? J1  Connector Type  RJ45  Number of Ports  1  Number of Rows  1  Applications  10/100 Base-TX  Mounting Type  Through Hole  Orientation  90° Angle (Right)  Termination  Height Above Board  0.550" (13.97mm)  LED Color  Number of Cores per Jack  5  Shielding  Shielded
Modular Connectors - Jacks With Magnetics  Package - Series PULSEJACK? J1  Connector Type RJ45  Number of Ports 1  Number of Rows 1  Applications 10/100 Base-TX  Mounting Type Through Hole Orientation 90° Angle (Right)  Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack Shielding Shielded
Package - Series PULSEJACK? J1 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 5 Shielding Shielded
Series PULSEJACK? J1 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 5 Shielding Shielded
Connector Type RJ45  Number of Ports 1  Number of Rows 1  Applications 10/100 Base-TX  Mounting Type Through Hole  Orientation 90° Angle (Right)  Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
Number of Ports  Number of Rows  1 Applications  10/100 Base-TX  Mounting Type  Through Hole  Orientation  90° Angle (Right)  Termination  Solder  Height Above Board  0.550" (13.97mm)  LED Color  Green - Yellow  Number of Cores per Jack  Shielding  Shielded
Number of Rows 1 Applications 10/100 Base-TX  Mounting Type Through Hole Orientation 90° Angle (Right)  Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
Applications 10/100 Base-TX  Mounting Type Through Hole Orientation 90° Angle (Right)  Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.550" (13.97mm) LED Color Green - Yellow Number of Cores per Jack 5 Shielding Shielded
Orientation 90° Angle (Right)  Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
Termination Solder  Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
Height Above Board 0.550" (13.97mm)  LED Color Green - Yellow  Number of Cores per Jack 5  Shielding Shielded
LED Color Green - Yellow Number of Cores per Jack 5 Shielding Shielded
Number of Cores per Jack 5 Shielding Shielded
Shielding Shielded
ē .
Features Board Guide
Tab Direction Up
Contact Material Phosphor Bronze
Contact Finish Gold
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Report errors?

### J1026F01P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## J1026F01P Payment Methods



















## J1026F01P Shipping Methods













If you have any question about J1026F01P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com