



J7AN-E9-DC12 Information

Heisener.com

Part Number J7AN-E9-DC12

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR 3PST 15A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









J7AN-E9-DC12 Specifications

Manufacturer Part NumberJ7AN-E9-DC12ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesJ7ANRelay TypeContactorCoil TypeNon LatchingCoil Current66.7mACoil Voltage12VDCContact Form3PST (3 Form A)Contact Rating (Current)15ASwitching Voltage600VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time100msRelease Time30msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal		
Category Relays Power Relays, Over 2 Amps Package - Series J7AN Relay Type Contactor Coil Type Non Latching Coil Current 66.7mA Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer Part Number	J7AN-E9-DC12
Package - Series J7AN Relay Type Contactor Coil Type Non Latching Coil Current 66.7mA Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer	Omron Automation and Safety
Package - Series J7AN Relay Type Contactor Coil Type Non Latching Coil Current 66.7mA Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Category	Relays
Series J7AN Relay Type Contactor Coil Type Non Latching Coil Current 66.7mA Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 66.7mA Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current66.7mACoil Voltage12VDCContact Form3PST (3 Form A)Contact Rating (Current)15ASwitching Voltage600VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time100msRelease Time30msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Series	J7AN
Coil Current66.7mACoil Voltage12VDCContact Form3PST (3 Form A)Contact Rating (Current)15ASwitching Voltage600VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time100msRelease Time30msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Relay Type	Contactor
Coil Voltage 12VDC Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form 3PST (3 Form A) Contact Rating (Current) 15A Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style 15A 600VAC - Max 9.6 VDC 1.2 VDC 1.2 VDC 100ms Screw Terminal	Coil Voltage	12VDC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	3PST (3 Form A)
Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	600VAC - Max
Operate Time 100ms Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	9.6 VDC
Release Time 30ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	1.2 VDC
Features - DIN Rail Termination Style Screw Terminal	Operate Time	100ms
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	-
·	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

J7AN-E9-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

J7AN-E9-DC12 Payment Methods



















J7AN-E9-DC12 Shipping Methods













If you have any question about J7AN-E9-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com