



J8064D668ANL Information

Heisener.com

Part Number J8064D668ANL

ManufacturerPulse Electronics NetworkCategoryConnectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 6PORT 100 BASE-TX

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









J8064D668ANL Specifications

| Manufacturer Part Number J8064D668ANL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J8 Connector Type RJ45 Number of Ports 6 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | | |
|--|--------------------------|---|
| Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J8 Connector Type RJ45 Number of Ports 6 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Manufacturer Part Number | J8064D668ANL |
| Package-SeriesPULSEJACK? J8Connector TypeRJ45Number of Ports6Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Manufacturer | Pulse Electronics Network |
| Package-SeriesPULSEJACK? J8Connector TypeRJ45Number of Ports6Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Category | Connectors, Interconnects |
| SeriesPULSEJACK? J8Connector TypeRJ45Number of Ports6Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | | Modular Connectors - Jacks With Magnetics |
| Connector TypeRJ45Number of Ports6Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Package | - |
| Number of Ports 6 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Series | PULSEJACK? J8 |
| Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Connector Type | RJ45 |
| Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Number of Ports | 6 |
| Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Number of Rows | 1 |
| Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Applications | 10/100 Base-TX, AutoMDIX |
| Termination Solder Height Above Board 0.536" (13.61mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Mounting Type | Through Hole |
| Height Above Board LED Color Green - Yellow Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Orientation | 90° Angle (Right) |
| LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Termination | Solder |
| Number of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C | Height Above Board | 0.536" (13.61mm) |
| Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | LED Color | Green - Yellow |
| Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C | Number of Cores per Jack | 4 |
| Tab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C | Shielding | Shielded, EMI Finger |
| Contact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C | Features | Board Guide |
| Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ | Tab Direction | Down |
| Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ | Contact Material | Phosphor Bronze |
| | Contact Finish | Gold |
| Report errors? | Operating Temperature | 0°C ~ 70°C |
| | | Report errors? |

J8064D668ANL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

J8064D668ANL Payment Methods



















J8064D668ANL Shipping Methods













If you have any question about J8064D668ANL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com