



J8064E64NL Information



For Reference Only

Part Number J8064E64NL

Manufacturer Pulse Electronics Network
Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 4PORT 100 BASE-TX

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









J8064E64NL Specifications

Manufacturer Part Number Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package PulsEJACK? J8 Connector Type RJ45 Number of Ports Applications I0/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination LED Color Number of Cores per Jack Ahielding Shielded, EMI Finger Features Board Guide Contact Material Contact Material Operating Temperature PulsE Electronics Network Modular Connectors Pulse Electronics Network Modular Connectors Jacks With Magnetics Pulse Electronics Network Modular Connectors Jacks With Magnetics Ads With Magnetics Pulse Electronics Network Modular Connectors Jacks With Magnetics Ads With Magnetics Pulse Electronics Network Modular Connectors Jacks With Magnetics Ads With Magnetics Pulse Shields With Magnetics Ads With Magnetics Ads With Magnetics Pulse Shields With Magnetics Ads With All Action Address A		
Canectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J8 Connector Type RJ45 Number of Ports 4 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 10.536" (13.61mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Contact Material Down Contact Material Contact Finish Gold Operating Temperature O"C ~ 70°C	Manufacturer Part Number	J8064E64NL
Package-SeriesPULSEJACK? J8Connector TypeRJ45Number of Ports4Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	Pulse Electronics Network
Package-SeriesPULSEJACK? J8Connector TypeRJ45Number of Ports4Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
Series PULSEJACK? J8 Connector Type RJ45 Number of Ports 4 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports4Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Package	-
Number of Ports4Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Series	PULSEJACK? J8
Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Does Not Contain LED Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Operating Temperature	Number of Ports	4
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.536" (13.61mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.536" (13.61mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°°C ~ 70°C	Applications	10/100 Base-TX, AutoMDIX
Termination Solder Height Above Board 0.536" (13.61mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Does Not Contain LED Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Orientation	90° Angle (Right)
LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 4 Contact Material April 1 Operating Temperature 4 Contact Finish April 2 Contact Finish April 3 Operating Temperature 4 Contact Finish April 2 Contact Finish April 3 Operating Temperature 4 Contact Finish April 2 Contact Finish April 3 Operating Temperature	Height Above Board	0.536" (13.61mm)
Shielding Shielded, EMI Finger Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Does Not Contain LED
Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	4
Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Shielding	Shielded, EMI Finger
Contact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Features	Board Guide
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Down
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

J8064E64NL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

J8064E64NL Payment Methods



















J8064E64NL Shipping Methods













If you have any question about J8064E64NL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com