

JA1A-TMP-AC115V

JA1A-TMP-AC115V Information

Heisener.com

Part Number JA1A-TMP-AC115V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 15A 115V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JA1A-TMP-AC115V Specifications

Manufacturer Part Number JAIA-TMP-AC115V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JA Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 115VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage115VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	JA1A-TMP-AC115V
Package - Series JA Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 115VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package - Series JA Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 115 VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250 VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series JA Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 115VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage115VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current12mACoil Voltage115VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Series	JA
Coil Current Coil Voltage 115VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 12mA SPST-NO (1 Form A) 15A SPST-NO (1 Form	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Current	12mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 15A 250VAC - Max 92 VAC 10ms 34.5 VAC 10ms 2ms Features - Mounting Type Through Hole PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Voltage	115VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	15A
Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Max
Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	92 VAC
Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	34.5 VAC
Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Release Time	2ms
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
		Report errors?

JA1A-TMP-AC115V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JA1A-TMP-AC115V Payment Methods



















JA1A-TMP-AC115V Shipping Methods













If you have any question about JA1A-TMP-AC115V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com