



JANTX1N5622 Information

Heisener.com

Part Number JANTX1N5622

Manufacturer Microsemi Corporation

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 1KV 1A AXIAL

Package A, Axial

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JANTX1N5622 Specifications

Manufacturer Part NumberJANTX1N5622ManufacturerMicrosemi CorporationCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageA, AxialSeriesMilitary, MIL-PRF-19500/427Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.3V @ 3ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)2μs
Category Discrete Semiconductor Products Diodes - Rectifiers - Single A, Axial Series Military, MIL-PRF-19500/427 Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery >500ns, > 200mA (Io)
Diodes - Rectifiers - Single Package A, Axial Series Military, MIL-PRF-19500/427 Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1000V Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery > 500ns, > 200mA (Io)
Package A, Axial Series Military, MIL-PRF-19500/427 Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1000V Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery >500ns, > 200mA (Io)
Series Military, MIL-PRF-19500/427 Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1000V Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery >500ns, > 200mA (Io)
Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery >500ns, > 200mA (Io)
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Standard Recovery > 500ns, > 200mA (Io)
Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Standard Recovery >500ns, > 200mA (Io)
Voltage - Forward (Vf) (Max) @ If Speed 1.3V @ 3A Standard Recovery >500ns, > 200mA (Io)
Speed Standard Recovery >500ns, > 200mA (Io)
Reverse Recovery Time (trr) 2us
To tolde Recovery Time (at)
Current - Reverse Leakage @ Vr 500nA @ 1000V
Capacitance @ Vr, F
Mounting Type Through Hole
Package / Case A, Axial
Supplier Device Package -
Operating Temperature - Junction -65°C ~ 200°C
Report errors?

JANTX1N5622 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JANTX1N5622 Payment Methods

































If you have any question about JANTX1N5622, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com