

JANTXV1N5711UR-1

JANTXV1N5711UR-1 Information



For Reference Only

Part Number JANTXV1N5711UR-1 Manufacturer Microsemi Corporation

Category Discrete Semiconductor Products
Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 50V 33MA DO213AA

Package DO-213AA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JANTXV1N5711UR-1 Specifications

Manufacturer Part Number Manufacturer Microsemi Corporation Discrete Semiconductor Products Diodes - Rectifiers - Single Package DO-213AA Series Military, MIL-PRF-19500/444 Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Microsemi Corporation Microsemi Corporation Microsemi Corporation Alicrosemi Cor		
Category Discrete Semiconductor Products Diodes - Rectifiers - Single Package DO-213AA Series Military, MIL-PRF-19500/444 Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Diodes - Rectifiers - Single Military, MIL-PRF-19500/444 Military, MIL-PRF-19500/444 Schottky 50V - 200 A @ 50V 200 A @ 50V 2pF @ 0V, 1MHz	Manufacturer Part Number	JANTXV1N5711UR-1
Diodes - Rectifiers - Single Package DO-213AA Series Military, MIL-PRF-19500/444 Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 33mA Voltage - Forward (Vf) (Max) @ If 410mV @ 1mA Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Manufacturer	Microsemi Corporation
Package DO-213AA Series Military, MIL-PRF-19500/444 Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 50V Current - Average Rectified (Io) 33mA Voltage - Forward (Vf) (Max) @ If 410mV @ 1mA Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200nA @ 50V Capacitance @ Vr, F 2pF @ 0V, 1MHz	Category	Discrete Semiconductor Products
Series Military, MIL-PRF-19500/444 Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 50V Current - Average Rectified (Io) 33mA Voltage - Forward (Vf) (Max) @ If 410mV @ 1mA Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200nA @ 50V Capacitance @ Vr, F 2pF @ 0V, 1MHz		Diodes - Rectifiers - Single
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 33mA Voltage - Forward (Vf) (Max) @ If 410mV @ 1mA Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Package	DO-213AA
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 410mV @ 1mA Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Series	Military, MIL-PRF-19500/444
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Voltage - DC Reverse (Vr) (Max)	50V
Speed Small Signal =< 200mA (Io), Any Speed Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200nA @ 50V Capacitance @ Vr, F 2pF @ 0V, 1MHz	Current - Average Rectified (Io)	33mA
Reverse Recovery Time (trr) Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Voltage - Forward (Vf) (Max) @ If	410mV @ 1mA
Current - Reverse Leakage @ Vr Capacitance @ Vr, F 200nA @ 50V 2pF @ 0V, 1MHz	Speed	Small Signal =< 200mA (Io), Any Speed
Capacitance @ Vr, F 2pF @ 0V, 1MHz	Reverse Recovery Time (trr)	-
	Current - Reverse Leakage @ Vr	200nA @ 50V
Mounting Type Surface Mount	Capacitance @ Vr, F	2pF @ 0V, 1MHz
~ · ·	Mounting Type	Surface Mount
Package / Case DO-213AA	Package / Case	DO-213AA
Supplier Device Package DO-213AA	Supplier Device Package	DO-213AA
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature - Junction	-65°C ~ 150°C
Report errors?		Report errors?

JANTXV1N5711UR-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JANTXV1N5711UR-1 Payment Methods



















JANTXV1N5711UR-1 Shipping Methods













If you have any question about JANTXV1N5711UR-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com