

JANTXV1N5804US

JANTXV1N5804US Information

Constant of the	Part Number	JANTXV1N5804US	
	Manufacturer	Microsemi Corporation	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	Line of the
	Description	DIODE GEN PURP 100V 1A D5A	ÿ,
	Package	SQ-MELF, A	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Re



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



JANTXV1N5804US Specifications

ManufacturerMicrosemi CorporationCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageSQ-MELF, ASeriesMilitary, MIL-PRF-19500/477Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If875mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, FSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction65°C ~ 175°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageSQ-MELF, ASeriesMilitary, MIL-PRF-19500/477Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If875mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	JANTXV1N5804US
Diodes - Rectifiers - SinglePackageSQ-MELF, ASeriesMilitary, MIL-PRF-19500/477Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If875mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1 μ A @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Manufacturer	Microsemi Corporation
PackageSQ-MELF, ASeriesMilitary, MIL-PRF-19500/477Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If875mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesMilitary, MIL-PRF-19500/477Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If $875mV @ 1A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1 $\mu A @ 100V$ Capacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction $-65°C ~ 175°C$		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If $875mV @ 1A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Package	SQ-MELF, A
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If $875mV @ 1A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $25ns$ Current - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F $25pF @ 10V, 1MHz$ Mounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction $-65°C ~ 175°C$	Series	Military, MIL-PRF-19500/477
Current - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If875mV @ 1ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $875mV @ 1A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $25ns$ Current - Reverse Leakage @ Vr $1\muA @ 100V$ Capacitance @ Vr, F $25pF @ 10V, 1MHz$ Mounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction -65° C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	100V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $25ns$ Current - Reverse Leakage @ Vr $1\mu A$ @ 100VCapacitance @ Vr, F $25pF$ @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$	Current - Average Rectified (Io)	1A
Reverse Recovery Time (trr)25nsCurrent - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	875mV @ 1A
Current - Reverse Leakage @ Vr1µA @ 100VCapacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F25pF @ 10V, 1MHzMounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Reverse Recovery Time (trr)	25ns
Mounting TypeSurface MountPackage / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Current - Reverse Leakage @ Vr	1µA @ 100V
Package / CaseSQ-MELF, ASupplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Capacitance @ Vr, F	25pF @ 10V, 1MHz
Supplier Device PackageD-5AOperating Temperature - Junction-65°C ~ 175°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Package / Case	SQ-MELF, A
	Supplier Device Package	D-5A
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

JANTXV1N5804US Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

JANTXV1N5804US Payment Methods



JANTXV1N5804US Shipping Methods



If you have any question about JANTXV1N5804US, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com