



JB5CS05AM00N Information



For Reference Only

Part Number JB5CS05AM00N Manufacturer JAE Electronics

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT WATERPROOF 5POS T/H

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JB5CS05AM00N Specifications

Manufacturer Part NumberJBSCS05AM00NManufacturerJAE ElectronicsCategoryConnectors, InterconnectsPackage-SeriesJB5Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A		
CategoryConnectors, InterconnectsPackage-SeriesJB5Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Manufacturer Part Number	JB5CS05AM00N
Package-SeriesJB5Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Manufacturer	JAE Electronics
Package-SeriesJB5Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Category	Connectors, Interconnects
SeriesJB5Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Package	-
Number of Positions5Shell Size - InsertSShell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Series	JB5
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Number of Positions	5
Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishCopper, Chromium PlatedContact FinishGoldFeatures-Voltage - Rated320VACCurrent Rating3A	Shell Size - Insert	S
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead; Through Hole
Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Termination	Solder
Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Fastening Type	Push-Pull
Shell Material, Finish Copper, Chromium Plated Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Orientation	Keyed
Contact Finish Gold Features - Voltage - Rated 320VAC Current Rating 3A	Ingress Protection	IP68 - Dust Tight, Waterproof
Features - Voltage - Rated 320VAC Current Rating 3A	Shell Material, Finish	Copper, Chromium Plated
Voltage - Rated 320VAC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
-	Voltage - Rated	320VAC
Report errors?	Current Rating	3A
		Report errors?

JB5CS05AM00N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JB5CS05AM00N Payment Methods



















JB5CS05AM00N Shipping Methods













If you have any question about JB5CS05AM00N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com