



JBB25DYHD Information

Heisener.com

Part Number JBB25DYHD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 50POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBB25DYHD Specifications

Manufacturer Part Number JBB25DYHD Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	3DD23D TIID Specifications		
Card Edge Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	JBB25DYHD	
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card Type	Package	-	
Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-	
Number of Positions/Bay/Row Solder, Staggered Contact Finish Thickness Contact Type Color Flange Feature Number of Positions 50 0.062" (1.57mm) 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features	Number of Positions/Bay/Row	25	
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	50	
Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.050" (1.27mm)	
Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-	
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder, Staggered	
Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Beryllium Copper	
Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Cantilever	
	Color	Black	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 150°C	
Report errors		Report error	rs?

JBB25DYHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBB25DYHD Payment Methods



















JBB25DYHD Shipping Methods













If you have any question about JBB25DYHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com