

JBB30DYRN

uest a Quote

JBB30DYRN Information

Heisener.com	Part Number	JBB30DYRN	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	5
	Description	CONN EDGE DUAL FMALE 60POS 0.050	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



JBB30DYRN Specifications

ManufacturerSullins Connector SolutionsCardegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesGord Edge, Straddle MountNounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIopin (0.25µm)Contact TypeGataleverContact TypeGataleverContact TypeSolderContact TypeGoldContact TypeGoldContact TypeSolareverContact TypeSolareverCon	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Number of Rows2PitchSolderMounting TypeBoard Edge, Straddle MountContact MaterialGoldContact Finish ThicknessIojuin (0.25µm)Contact TypeGaileverContact TypeCantileverContact TypeBlackFaquere-ColorBlackFaquere-Coperating Temperature-65°C ~ 150°C	Manufacturer Part Number	JBB30DYRN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCardileverColoar TypeCardileverColoar TypeCardileverColoar TypeSolderContact TypeCardileverColoar TypeCardileverColoar TypeBlackFinage Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-6%°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish ThicknessGoldContact Finish ThicknessIpµin (0.25µm)Contact TypeBackColorBlackFage Feature-Operating Temperature-Operating Temperature-Solder-Contact TypeSolderContact Type-ColorBlackFage Feature-Operating Temperature-Solder-Contact Type-Contact Type-ColorSolder<		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIquin (0.25µm)Contact TypeBackFlange Feature-Operating Temperature65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCardileverColorBlackFlange Feature-Operating Temperature-55°C ~ 150°C	Series	-
Number of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeEartleverColorBlackFlange Feature-Operating Temperature-5°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish ThicknessIuµin (0.25µm)Contact TypeCardileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	30
Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	60
Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeInpin (0.25µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeBackColorBlackFlange Feature-Operating Temperatures-55°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
	Operating Temperature	-65°C ~ 150°C
Report errors?		Report errors?

JBB30DYRN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

JBB30DYRN Payment Methods

JBB30DYRN Shipping Methods



If you have any question about JBB30DYRN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com