



# **JBB35DYRQ Information**

Heisener.com

Part Number JBB35DYRQ

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 70POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **JBB35DYRO Specifications**

Manufacturer Part Number         JBB35DYRQ           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish Thickness         10µin (0.25µm)           Contact Finish Thickness         10µin (0.25µm)           Cotor         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 150°C	abbash i KQ Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Cantilever           Color         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 150°C	Manufacturer Part Number	JBB35DYRQ
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row       35         Number of Positions       70         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       Card Extender         Mounting Type       Board Edge, Straddle Mount         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)         Operating Temperature       -65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features Card Extender  Mounting Type Board Edge, Straddle Mount  Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color Black  Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)  Operating Temperature -65°C ~ 150°C	Number of Positions/Bay/Row	35
Number of Rows2Pitch $0.050"$ (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, $0.078"$ (1.98mm)Operating Temperature $-65^{\circ}$ C ~ $150^{\circ}$ C	Number of Positions	70
Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature $-65$ °C $\sim 150$ °C	Pitch	0.050" (1.27mm)
Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color Black  Flange Feature Straddle Mount Opening, Unthreaded, $0.078" (1.98mm)$ Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, $0.078$ " (1.98mm)Operating Temperature $-65$ °C ~ $150$ °C	Mounting Type	Board Edge, Straddle Mount
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Cantilever  Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Straddle Mount Opening, Unthreaded, $0.078"$ (1.98mm)  Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

### **JBB35DYRQ** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **JBB35DYRQ Payment Methods**



















## **JBB35DYRQ Shipping Methods**













If you have any question about JBB35DYRQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com