



JBB50DYHD Information

Heisener.com

Part Number JBB50DYHD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 100POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBB50DYHD Specifications

Manufacturer Part Number Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Contact Type Contact Type Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	3DD30D 111D Specifications	
Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black	Manufacturer Part Number	JBB50DYHD
Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Contact Finish Gold Contact Type Contact Type Cantilever Color Black	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black		Card Edge Connectors - Edgeboard Connectors
Card Type Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black	Package	-
Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Series	-
Number of Positions 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black	Card Type	Non Specified - Dual Edge
Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Gender	Female
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Number of Positions/Bay/Row	50
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Number of Positions	100
Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black	Number of Rows	2
Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Pitch	0.050" (1.27mm)
Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Features	-
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black	Mounting Type	Through Hole
Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black	Termination	Solder, Staggered
Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black	Contact Material	Beryllium Copper
Contact Type Cantilever Color Black	Contact Finish	Gold
Color Black	Contact Finish Thickness	10μin (0.25μm)
	Contact Type	Cantilever
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Color	Black
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature	-65°C ~ 150°C
Report errors		Report errors?

JBB50DYHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBB50DYHD Payment Methods



















JBB50DYHD Shipping Methods













If you have any question about JBB50DYHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com