



### **JBB66DYHN Information**

Heisener.com

Part Number JBB66DYHN

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 132POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **JBB66DYHN Specifications**

Manufacturer Part Number         JBB66DYHN           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         66           Number of Positions         132           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         -           Mounting Type         Through Hole           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 150°C	3DD00D 1111 (Specifications	
Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       66         Number of Positions       132         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Type       Cantilever         Color       Black         Flange Feature       -         Operating Temperature       -65°C ~ 150°C	Manufacturer Part Number	JBB66DYHN
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         66           Number of Positions         132           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         -           Mounting Type         Through Hole           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         66           Number of Positions         132           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         -           Mounting Type         Through Hole           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 150°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         66           Number of Positions         132           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         -           Mounting Type         Through Hole           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Package	-
Gender         Female           Number of Positions/Bay/Row         66           Number of Positions         132           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         -           Mounting Type         Through Hole           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row  132 Card Thickness  0.062" (1.57mm)  Number of Rows  2 Pitch  0.050" (1.27mm)  Features  - Mounting Type  Through Hole  Termination  Solder, Staggered  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Cantilever  Color  Black  Flange Feature  - Operating Temperature  65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	66
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	132
Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Operating Temperature  -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Color Black Flange Feature - Coperating Temperature - Cost	Termination	Solder, Staggered
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Black Flange Feature Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Color Black Flange Feature Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

#### **JBB66DYHN** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **JBB66DYHN Payment Methods**



















### **JBB66DYHN Shipping Methods**













If you have any question about JBB66DYHN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com