



JBC20HEYH Information

Heisener.com

Part Number JBC20HEYH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 20POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBC20HEYH Specifications

Manufacturer Part Number JBC20HEYH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	3DC2011E111 Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ЈВС20НЕҮН	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	-	
Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	20	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	1	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125 " (3.18mm) DiaOperating Temperature -65 °C ~ 150 °C	Pitch	0.100" (2.54mm)	
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 150 °C	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C	Termination	Solder	
Contact Finish Thickness 10 μ in (0.25 μ m) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Material	Beryllium Copper	
Contact Type Cantilever Color - Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish	Gold	
Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 150°C	
			Report errors?

JBC20HEYH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBC20HEYH Payment Methods





















JBC20HEYH Shipping Methods













If you have any question about JBC20HEYH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com