

JBXEA2G08FPSDS

JBXEA2G08FPSDS Information

Heisener.com

Part Number JBXEA2G08FPSDS

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS PNL MNT SKT PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXEA2G08FPSDS Specifications

Manufacturer Part NumberJBXEA2G08FPSDSManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A		
CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Manufacturer Part Number	JBXEA2G08FPSDS
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Manufacturer	Souriau
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Package	-
Number of Positions8Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Series	JBX
Shell Size - Insert 2 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated Current Rating 10A	Number of Positions	8
Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated830VDCCurrent Rating10A	Shell Size - Insert	2
Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Mounting Type	Panel Mount, Bulkhead; Through Hole
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Termination	Solder
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Brass, Chrome over Nickel Gold Shielded 10A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated 830VDC Current Rating 10A	Ingress Protection	IP40
Features Shielded Voltage - Rated 830VDC Current Rating 10A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 830VDC Current Rating 10A	Contact Finish	Gold
Current Rating 10A	Features	Shielded
	Voltage - Rated	830VDC
Report errors?	Current Rating	10A
		Report errors?

JBXEA2G08FPSDS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXEA2G08FPSDS Payment Methods





















JBXEA2G08FPSDS Shipping Methods













If you have any question about JBXEA2G08FPSDS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com