

JBXEA2G18FPSDS

JBXEA2G18FPSDS Information

Heisener.com

Part Number JBXEA2G18FPSDS

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 18POS PNL MNT SKT PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXEA2G18FPSDS Specifications

Manufacturer Part Number JBXEA2G18FPSDS Manufacturer Souriau Category Connectors, Interconnects Package - Series JBX Connector Type Receptacle, Female Sockets Number of Positions 18 Shell Size - Insert 2 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A		
CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A	Manufacturer Part Number	JBXEA2G18FPSDS
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660 VDCCurrent Rating5.5A	Manufacturer	Souriau
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A	Package	-
Number of Positions18Shell Size - Insert2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A	Series	JBX
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated Ge0VDC Current Rating Solder Panel Mount, Bulkhead; Through Hole Solder Push-Pull Gold G Cortent Solder Solder Shielded Solder S	Number of Positions	18
Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated660VDCCurrent Rating5.5A	Shell Size - Insert	2
Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Mounting Type	Panel Mount, Bulkhead; Through Hole
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Termination	Solder
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Gold Gold Shielded 5.5A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Ingress Protection	IP40
Features Shielded Voltage - Rated 660VDC Current Rating 5.5A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 660VDC Current Rating 5.5A	Contact Finish	Gold
Current Rating 5.5A	Features	Shielded
	Voltage - Rated	660VDC
Report errors?	Current Rating	5.5A
		Report errors?

JBXEA2G18FPSDS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXEA2G18FPSDS Payment Methods



















JBXEA2G18FPSDS Shipping Methods













If you have any question about JBXEA2G18FPSDS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com