

JBXER0G05MSSDSR

JBXER0G05MSSDSR Information

Heisener.com

Part Number JBXER0G05MSSDSR

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 5POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXER0G05MSSDSR Specifications

Manufacturer Part Number JBXEROGO5MSSDSR Manufacturer Souriau Category Connectors, Interconnects Package - Series JBX Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A		
Category Circular Connectors Package - Series JBX Connector Type Receptacle, Male Pins Number of Positions Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Voltage - Rated Voltage - Rated Ucrrent Rating Connectors, Interconnects Circular Connectors	Manufacturer Part Number	JBXER0G05MSSDSR
Circular Connectors Package - Series JBX Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating Genace IBX Receptacle, Male Pins Sold Receptacle, Male Pins BX GO G Receptacle, Male Pins B Receptacle, Male Pins B Receptacle, Male Pins B Receptacle, Male Pins Shell Material, Finish G G Solder Cup Push-Pull Orientation G Shielded Voltage - Rated Gold Current Rating Gold Current Rating	Manufacturer	Souriau
Package - JBX Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert0Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated400VDCCurrent Rating6.5A		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Package	-
Number of Positions5Shell Size - Insert0Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated400VDCCurrent Rating6.5A	Series	JBX
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Number of Positions	5
Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Shell Size - Insert	0
Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating IP40 Brass, Chrome over Nickel Gold Gold Shielded 6.5A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Brass, Chrome over Nickel Gold 400VDC 6.5A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Ingress Protection	IP40
Features Shielded Voltage - Rated 400VDC Current Rating 6.5A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 400VDC Current Rating 6.5A	Contact Finish	Gold
Current Rating 6.5A	Features	Shielded
-	Voltage - Rated	400VDC
Report errors?	Current Rating	6.5A
		Report errors?

JBXER0G05MSSDSR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXER0G05MSSDSR Payment Methods



















JBXER0G05MSSDSR Shipping Methods













If you have any question about JBXER0G05MSSDSR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com