

# JBXER0J03MCSDSR

### JBXER0J03MCSDSR Information

Heisener.com

Part Number JBXER0J03MCSDSR

Manufacturer Souriau

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS PNL MNT PIN CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# JBXER0J03MCSDSR Specifications

Manufacturer     JBXER0J03MCSDSR       Manufacturer     Souriau       Category     Connectors, Interconnects       Package     -       Series     JBX       Connector Type     Receptacle, Male Pins       Number of Positions     3       Shell Size - Insert     0       Shell Size, MIL     -       Mounting Type     Panel Mount, Bulkhead - Rear Side Nut       Termination     Crimp       Fastening Type     Push-Pull       Orientation     J       Ingress Protection     IP40       Shell Material, Finish     Brass, Chrome over Nickel       Contact Finish     Gold       Features     Shielded       Voltage - Rated     600VDC       Current Rating     8A		
Category Circular Connectors  Package - Series JBX Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation J Ingress Protection Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating Series  Circular Connectors  - Connectors Interconnects Circular Connectors - Circular Connectors  - Connectors Interconnects Circular Connectors - Connector Sinterconnects - Circular Connectors - Circular Connect	Manufacturer Part Number	JBXER0J03MCSDSR
Circular Connectors  Package - Series JBX Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 0 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated Current Rating  Section  Crimation Circular Connectors  JBX Receptacle, Male Pins A Beceptacle, Male Pins A Beceptacle, Male Pins  Beceptacle, Male Packet Male Packet Male Packet Male Packet Male Packet Male Packe	Manufacturer	Souriau
Package-SeriesJBXConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert0Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationCrimpFastening TypePush-PullOrientationJIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated600VDCCurrent Rating8A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert0Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationCrimpFastening TypePush-PullOrientationJIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated600VDCCurrent Rating8A		Circular Connectors
Connector Type Receptacle, Male Pins  Number of Positions 3  Shell Size - Insert 0  Shell Size, MIL -  Mounting Type Panel Mount, Bulkhead - Rear Side Nut  Termination Crimp  Fastening Type Push-Pull  Orientation J  Ingress Protection IP40  Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold  Features Shielded  Voltage - Rated 600VDC  Current Rating 8A	Package	-
Number of Positions3Shell Size - Insert0Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationCrimpFastening TypePush-PullOrientationJIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesShieldedVoltage - Rated600VDCCurrent Rating8A	Series	JBX
Shell Size - Insert  Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Rear Side Nut  Crimp Fastening Type Push-Pull Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold Features Shielded  Voltage - Rated Current Rating 8A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Rear Side Nut  Crimp Fastening Type Push-Pull Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated Current Rating 8A	Number of Positions	3
Mounting Type Panel Mount, Bulkhead - Rear Side Nut  Termination Crimp  Fastening Type Push-Pull  Orientation J  Ingress Protection IP40  Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold  Features Shielded  Voltage - Rated 600VDC  Current Rating 8A	Shell Size - Insert	0
Termination Crimp Fastening Type Push-Pull Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 600VDC Current Rating 8A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 600VDC Current Rating 8A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation J Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Shielded Voltage - Rated 600VDC Current Rating 8A	Termination	Crimp
Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  IP40  Brass, Chrome over Nickel  Gold  Gold  Shielded  Shielded  600VDC	Fastening Type	Push-Pull
Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Brass, Chrome over Nickel  Gold  600VDC  8A	Orientation	J
Contact Finish Gold Features Shielded Voltage - Rated 600VDC Current Rating 8A	Ingress Protection	IP40
Features Shielded  Voltage - Rated 600VDC  Current Rating 8A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 600VDC Current Rating 8A	Contact Finish	Gold
Current Rating 8A	Features	Shielded
-	Voltage - Rated	600VDC
Report errors?	Current Rating	8A
		Report errors?

### JBXER0J03MCSDSR Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## JBXER0J03MCSDSR Payment Methods





















### JBXER0J03MCSDSR Shipping Methods













If you have any question about JBXER0J03MCSDSR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com