

Heisener.com

JBXFC1G04FCSDSMR

JBXFC1G04FCSDSMR Information

Part Number JBXFC1G04FCSDSMR

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS RA INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXFC1G04FCSDSMR Specifications

Manufacturer Part Number Manufacturer Souriau Category Connectors, Interconnects Circular Connectors Package - Series JBX Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert I Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Gold Features Cable Clamp, Shielded Voltage - Rated Voltage - Rated Ournett Rating Penort arrors? Penort arrors?		
CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Manufacturer Part Number	JBXFC1G04FCSDSMR
Package-SeriesJBXConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Manufacturer	Souriau
Package-SeriesJBXConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Category	Connectors, Interconnects
SeriesJBXConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Package	-
Number of Positions4Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Series	JBX
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated Onow DOVDC Current Rating	Number of Positions	4
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated900VDCCurrent Rating10A	Shell Size - Insert	1
Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Termination	Crimp
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Orientation	G
Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Ingress Protection	IP40
Features Cable Clamp, Shielded Voltage - Rated 900VDC Current Rating 10A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 900VDC Current Rating 10A	Contact Finish	Gold
Current Rating 10A	Features	Cable Clamp, Shielded
	Voltage - Rated	900VDC
Report errors?	Current Rating	10A
Report crists:		Report errors?

JBXFC1G04FCSDSMR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXFC1G04FCSDSMR Payment Methods



















JBXFC1G04FCSDSMR Shipping Methods













If you have any question about JBXFC1G04FCSDSMR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com