

JBXSA2G16FCSDS

JBXSA2G16FCSDS Information

Heisener.com

Part Number JBXSA2G16FCSDS

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 16POS PNL MNT SKT CRMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXSA2G16FCSDS Specifications

Manufacturer Part Number JBXSA2G16FCSDS Manufacturer Souriau Category Connectors, Interconnects Package - Series JBX Connector Type Receptacle, Female Sockets Number of Positions 16 Shell Size - Insert 2 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A			
Category Circular Connectors Package - Series JBX Connector Type Receptacle, Female Sockets Number of Positions 16 Shell Size - Insert 2 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated Tyrel Circular Connectors Circular Connectors LBA Connectors	Manufacturer Part Number	JBXSA2G16FCSDS	
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - Insert2Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side NutTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated730VDCCurrent Rating6A	Manufacturer	Souriau	
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - Insert2Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side NutTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated730VDCCurrent Rating6A	Category	Connectors, Interconnects	
Series JBX Connector Type Receptacle, Female Sockets Number of Positions 16 Shell Size - Insert 2 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 66		Circular Connectors	
Connector Type Receptacle, Female Sockets Number of Positions 16 Shell Size - Insert 2 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Package	-	
Number of Positions Shell Size - Insert 2 Shell Size, MIL Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Series	JBX	
Shell Size - Insert 2 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Connector Type	Receptacle, Female Sockets	
Shell Size, MIL Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Number of Positions	16	
Mounting Type Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Shell Size - Insert	2	
Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Shell Size, MIL	-	
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Mounting Type	Free Hanging (In-Line); Panel Mount, Bulkhead - Front and Rear Side Nut	
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Termination	Crimp	
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Fastening Type	Push-Pull	
Shell Material, Finish Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Orientation	G	
Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Ingress Protection	IP40	
Features Cable Clamp, Shielded Voltage - Rated 730VDC Current Rating 6A	Shell Material, Finish	Brass, Chrome over Nickel	
Voltage - Rated 730VDC Current Rating 6A	Contact Finish	Gold	
Current Rating 6A	Features	Cable Clamp, Shielded	
	Voltage - Rated	730VDC	
Report errors?	Current Rating	6A	
			Report errors?

JBXSA2G16FCSDS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXSA2G16FCSDS Payment Methods



















JBXSA2G16FCSDS Shipping Methods













If you have any question about JBXSA2G16FCSDS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com