

Heisener.com

# JBXSR1G02FCSDSMR

### **JBXSR1G02FCSDSMR Information**

Part Number JBXSR1G02FCSDSMR

Manufacturer Souriau

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 2POS PNL MNT SKT CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# JBXSR1G02FCSDSMR Specifications

Manufacturer Part Number  Manufacturer  Souriau  Category  Connectors, Interconnects  Circular Connectors  Package  - Series  JBX  Connector Type  Receptacle, Female Sockets  Number of Positions  2 Shell Size - Insert  1 Shell Size, MIL  - Mounting Type  Free Hanging (In-Line); Panel Mount  Termination  Crimp  Fastening Type  Push-Pull  Orientation  G Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Voltage - Rated  Current Rating  Tenner Special Sockets  - Connectors  JBX  Receptacle, Female Sockets  JBX  Connector Finish  Connector Type  Receptacle, Female Sockets  JBX  Connector Finish  Gold  Cable Clamp, Shielded  Voltage - Rated  T60VDC  Tenner Special Sockets  Souriau  Connectors  Souriau  Connectors  JBA  Connectors  Souriau  Connectors  Circular Connectors  Souriau  Connectors  Souriau  Connectors  Circular Connectors  Souriau  Connectors  Circular Connectors  Souriau  Connectors  Circular Connectors  Souriau  Connectors  Circular Connectors  Souriau  Connectors  Circular		
CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Manufacturer Part Number	JBXSR1G02FCSDSMR
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Manufacturer	Souriau
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Package	-
Number of Positions2Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Series	JBX
Shell Size - Insert1Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line); Panel Mount  Crimp Fastening Type Push-Pull  Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold Features Cable Clamp, Shielded  Voltage - Rated Tourrent Rating  15A	Number of Positions	2
Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated760VDCCurrent Rating15A	Shell Size - Insert	1
Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 760VDC Current Rating 15A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 760VDC Current Rating 15A	Mounting Type	Free Hanging (In-Line); Panel Mount
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 760VDC Current Rating 15A	Termination	Crimp
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 760VDC Current Rating 15A	Fastening Type	Push-Pull
Shell Material, Finish  Contact Finish  Gold  Features  Cable Clamp, Shielded  Voltage - Rated  760VDC  Current Rating  15A	Orientation	G
Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 760VDC Current Rating 15A	Ingress Protection	IP40
Features Cable Clamp, Shielded  Voltage - Rated 760VDC  Current Rating 15A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 760VDC Current Rating 15A	Contact Finish	Gold
Current Rating 15A	Features	Cable Clamp, Shielded
	Voltage - Rated	760VDC
Report errors?	Current Rating	15A
Report crisis:		Report errors?

### JBXSR1G02FCSDSMR Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## JBXSR1G02FCSDSMR Payment Methods



















## JBXSR1G02FCSDSMR Shipping Methods













If you have any question about JBXSR1G02FCSDSMR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com