

# JBXSR3G14FCSDSR

### **JBXSR3G14FCSDSR Information**

Heisener.com

Part Number JBXSR3G14FCSDSR

Manufacturer Souriau

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 14POS PNL MNT SKT CRMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# JBXSR3G14FCSDSR Specifications

| Manufacturer Part Number     JBXSR3G14FCSDSR       Manufacturer     Souriau       Category     Connectors, Interconnects       Package     -       Series     JBX       Connector Type     Receptacle, Female Sockets       Number of Positions     14       Shell Size - Insert     3       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line); Panel Mount       Termination     Crimp       Fastening Type     Push-Pull       Orientation     G       Ingress Protection     IP40       Shell Material, Finish     Brass, Chrome over Nickel       Contact Finish     Gold       Features     Cable Clamp, Shielded       Voltage - Rated     830VDC       Current Rating     9A |                          |                                     |
|--|--------------------------|-------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A  | Manufacturer Part Number | JBXSR3G14FCSDSR                     |
| Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A   | Manufacturer             | Souriau                             |
| Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A   | Category                 | Connectors, Interconnects           |
| SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A   |                          | Circular Connectors                 |
| Connector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A  | Package                  | -                                   |
| Number of Positions14Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A  | Series                   | JBX                                 |
| Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationCrimpFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated830VDCCurrent Rating9A   | Connector Type           | Receptacle, Female Sockets          |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line); Panel Mount  Crimp Fastening Type Push-Pull  Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold Features Cable Clamp, Shielded  Voltage - Rated SaoVDC  Current Rating Shell Mount Free Hanging (In-Line); Panel Mount  Crimp Free Hanging (In-Line); Panel Mount  Crimp  Free Hanging (In-Line); Panel Mount  Crimp  Gold  Climp Shielded  SaoVDC  Outcome Sand Sand Sand Sand Sand Sand Sand Sand  | Number of Positions      | 14                                  |
| Mounting Type Free Hanging (In-Line); Panel Mount  Termination Crimp  Fastening Type Push-Pull  Orientation G  Ingress Protection IP40  Shell Material, Finish Brass, Chrome over Nickel  Contact Finish Gold  Features Cable Clamp, Shielded  Voltage - Rated 830VDC  Current Rating 9A   | Shell Size - Insert      | 3                                   |
| Termination Crimp Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 830VDC Current Rating 9A  | Shell Size, MIL          | -                                   |
| Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 830VDC Current Rating 9A  | Mounting Type            | Free Hanging (In-Line); Panel Mount |
| Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 830VDC Current Rating 9A   | Termination              | Crimp                               |
| Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 830VDC Current Rating 9A   | Fastening Type           | Push-Pull                           |
| Shell Material, Finish  Contact Finish  Gold  Features  Cable Clamp, Shielded  Voltage - Rated  830VDC  Current Rating  9A   | Orientation              | G                                   |
| Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 830VDC Current Rating 9A  | Ingress Protection       | IP40                                |
| Features Cable Clamp, Shielded  Voltage - Rated 830VDC  Current Rating 9A  | Shell Material, Finish   | Brass, Chrome over Nickel           |
| Voltage - Rated 830VDC Current Rating 9A   | Contact Finish           | Gold                                |
| Current Rating 9A  | Features                 | Cable Clamp, Shielded               |
|  | Voltage - Rated          | 830VDC                              |
| Report errors?   | Current Rating           | 9A                                  |
|  |                          | Report errors?                      |

#### JBXSR3G14FCSDSR Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JBXSR3G14FCSDSR Payment Methods**



















## JBXSR3G14FCSDSR Shipping Methods













If you have any question about JBXSR3G14FCSDSR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com