

Heisener.com

JBXSR3G30FSSDSMR

JBXSR3G30FSSDSMR Information

Part Number JBXSR3G30FSSDSMR

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 30POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JBXSR3G30FSSDSMR Specifications

Manufacturer JBXSR3G30FSSDSMR Manufacturer Souriau Category Connectors, Interconnects Package - Series JBX Connector Type Receptacle, Female Sockets Number of Positions 30 Shell Size - Insert 3 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A		
CategoryConnectors, InterconnectsPackage-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Manufacturer Part Number	JBXSR3G30FSSDSMR
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Manufacturer	Souriau
Package-SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Category	Connectors, Interconnects
SeriesJBXConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Package	-
Number of Positions30Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Series	JBX
Shell Size - Insert3Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Number of Positions	30
Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP40Shell Material, FinishBrass, Chrome over NickelContact FinishGoldFeaturesCable Clamp, ShieldedVoltage - Rated400VDCCurrent Rating3.5A	Shell Size - Insert	3
Termination Solder Cup Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Mounting Type	Free Hanging (In-Line); Panel Mount
Orientation G Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Termination	Solder Cup
Ingress Protection IP40 Shell Material, Finish Brass, Chrome over Nickel Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Orientation	G
Contact Finish Gold Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Ingress Protection	IP40
Features Cable Clamp, Shielded Voltage - Rated 400VDC Current Rating 3.5A	Shell Material, Finish	Brass, Chrome over Nickel
Voltage - Rated 400VDC Current Rating 3.5A	Contact Finish	Gold
Current Rating 3.5A	Features	Cable Clamp, Shielded
	Voltage - Rated	400VDC
Donort arrows	Current Rating	3.5A
Report errors?		Report errors?

JBXSR3G30FSSDSMR Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JBXSR3G30FSSDSMR Payment Methods





















JBXSR3G30FSSDSMR Shipping Methods













If you have any question about JBXSR3G30FSSDSMR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com