



JCB35DYHR Information

Heisener.com

Part Number JCB35DYHR

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 70POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JCB35DYHR Specifications

Manufacturer Part Number JCB35DYHR Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature -65°C ~ 150°C Operating Temperature -65°C ~ 150°C	3CD35D TTIK Speementons	
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Coperating Temperature - Coperating Temperature - Coperating Temperature - Contact Singered - Contact Finish Coperating Temperature - Coperating Temperature - Contact Finish - Coperating Temperature - Contact Finish - Coperating Temperature - Coperating Temperature - Contact Finish - Contact Finish - Coperating Temperature - Coperating Temperature - Contact Finish - Contact Finish - Contact Finish - Contact Finish - Coperating Temperature - Coperating Temperature - Contact Finish -	Manufacturer Part Number	JCB35DYHR
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 35 Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row Number of Positions 70 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature Operating Temperature -65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	35
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	70
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	Board Lock
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder, Staggered
Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65° C $\sim 150^{\circ}$ C	Contact Material	Beryllium Copper
Contact Type Color Black Flange Feature - Operating Temperature - Contact Type Cantilever - Color Colo	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature - $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

JCB35DYHR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JCB35DYHR Payment Methods



















JCB35DYHR Shipping Methods













If you have any question about JCB35DYHR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com