



JCB66DYHN Information

Heisener.com

Part Number JCB66DYHN

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 132POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JCB66DYHN Specifications

Manufacturer Part Number JCB66DYHN Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C Report errors?	3 CD00D I III \ Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	JCB66DYHN
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 66 Number of Positions 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row 132 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature Operating Temperature 66°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	66
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Number of Positions	132
Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature Operating Temperature - 65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder, Staggered
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Cantilever Color Black Flange Feature - Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature - Generating Temperature -65°C ~ 150 °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

JCB66DYHN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JCB66DYHN Payment Methods

































If you have any question about JCB66DYHN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com