

JCR-18R Information

Heisener.com

Part Number JCR-18R
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE 7.2KV 9R M/S**Package**Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JCR-18R Specifications

Manufacturer Part Number Manufacturer Eaton Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series * Fuse Type Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Jirch 188 Circuit Protection Eaton Cartridge, Non-Standard O.118" Dia x 0.443" L (3.00mm x 11.24mm)		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeries*Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Manufacturer Part Number	JCR-18R
Package Cartridge, Non-Standard Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Category	Circuit Protection
Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)		Electrical, Specialty Fuses
Fuse Type - Current Rating - Current Rating - Current Rating - Collage Rating - AC - Current Rating - Collage Rating - DC - Current Rating - Collage Rating - DC - Current Rating - Collage Rating - DC - Current Response Time - Current Response Tim	Package	Cartridge, Non-Standard
Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Series	*
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features - Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - - Voltage Rating - AC - - - - - - - - - - - - -	Fuse Type	-
Voltage Rating - DC Response Time - Applications - Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension	Current Rating	-
Response Time Applications - Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Operating Temperature Operating Operating Temperature Operating Tempera	Voltage Rating - AC	-
Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - One Cartridge, Non-Standard	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Coperating Capacity @ Rated Voltage - Cartridge, Non-Standard Size / Dimension - Cartridge, Non-Standard - Cartridge, Non-	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage - Holder Case Cartridge, Non-Standard Size / Dimension - O.118" Dia x 0.443" L (3.00mm x 11.24mm)	Applications	-
Approvals Operating Temperature	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Class	-
Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 0.118" Dia x 0.443" L (3.00mm x 11.24mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Depart arrows	Size / Dimension	0.118" Dia x 0.443" L (3.00mm x 11.24mm)
Report errors?		Report errors?

JCR-18R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JCR-18R Payment Methods



















JCR-18R Shipping Methods













If you have any question about JCR-18R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com