

JCR-A-12R Information

Heisener.com

Part Number JCR-A-12R
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JCR-A-12R Specifications

Manufacturer Part NumberJCR-A-12RManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCR-AFuse TypeCartridgeCurrent Rating230AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.850" L (76.20mm x 402.60mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series JCR-A Fuse Type Cartridge Current Rating 230A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	JCR-A-12R
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series JCR-A Fuse Type Current Rating 230A Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Size / Dimension AC Cartridge, Non-Standard Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension Size / Dimension	Manufacturer	Eaton
Package Cartridge, Non-Standard Series JCR-A Fuse Type Cartridge Current Rating 230A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage UR Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3LCARCH CARCH C	Category	Circuit Protection
Series JCR-A Fuse Type Cartridge Current Rating 230A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 230A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Candon Cartridge Cartr	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 230A 7200V (7.2kV) - Response Time - UR Other Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Series	JCR-A
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 7200V (7.2kV) - 1000	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension	Current Rating	230A
Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Capacity (76.20mm x 402.60mm)	Voltage Rating - AC	7200V (7.2kV)
Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Response Time	-
Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Applications	Motor Protection
Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension UR Curridge Soka	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Class	R
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Approvals	UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 3.000" Dia x 15.850" L (76.20mm x 402.60mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 15.850" L (76.20mm x 402.60mm)
		Report errors?

JCR-A-12R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JCR-A-12R Payment Methods





















JCR-A-12R Shipping Methods













If you have any question about JCR-A-12R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com