

## **JCR-B-3R Information**

Heisener.com

Part Number JCR-B-3R
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CYLINDRICAL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JCR-B-3R Specifications**

Manufacturer Part Number         JCR-B-3R           Manufacturer         Eaton           Category         Circuit Protection           Flackage         Cylindrical, Blade Terminal (Bolt)           Series         JCR-B           Fuse Type         Cartridge           Current Rating         100A           Voltage Rating - AC         7200V (7.2kV)           Voltage Rating - DC         -           Response Time         -           Applications         Motor Protection           Features         Indicating           Class         R           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         50kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         17.88" Dia x 19.25" L (454.10mm x 488.90mm)    Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesJCR-BFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Manufacturer Part Number	JCR-B-3R
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series JCR-B Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt) Size / Dimension  ICLass Series	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesJCR-BFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Category	Circuit Protection
Series JCR-B Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1200A  Cartridge Cartridge Cartridge Cartridge Capacity Grape Capacity Grap		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 7200V (7.2kV)  Voltage Rating - DC	Series	JCR-B
Voltage Rating - AC  Voltage Rating - DC  Response Time  - Applications  Motor Protection  Features  Indicating  Class  R  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  7200V (7.2kV)  - Class  R  Approvals  UR  Features  Broaking Capacity @ Rated Voltage  Bolt Mount  Cylindrical, Blade Terminal (Bolt)  17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Applications  Motor Protection  Features  Indicating  Class  R  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension	Current Rating	100A
Response Time  Applications  Motor Protection  Features  Indicating  Class  R  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension	Voltage Rating - AC	7200V (7.2kV)
Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Voltage Rating - DC	-
Features Indicating  Class R  Approvals UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 50kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Response Time	-
Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Applications	Motor Protection
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  - CUR  Cylindrical, Blade Terminal (Bolt)  17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Class	R
Breaking Capacity @ Rated Voltage 50kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	17.88" Dia x 19.25" L (454.10mm x 488.90mm)
		Report errors?

### **JCR-B-3R Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JCR-B-3R Payment Methods**





















## **JCR-B-3R Shipping Methods**













If you have any question about JCR-B-3R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com